SIEMENS

Data sheet

6GK7443-1EX11-0XE0

product type designation



CP 443-1

*********** spare part ******** communications processor CP 443-1 for connection of SIMATIC S7-400 to industrial Ethernet via ISO/TCP/IP and UDP, S7 communication, fetch/write, diagnostics extensions, send/receive, with and without RFC1006, multicast, NTP, initialization via LAN, access protection via IP access list 10/100 Mbit.

transfer rate	
transfer rate	
at the 1st interface	10 100 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	1
number of electrical connections	
• at the 1st interface / according to Industrial Ethernet	1
type of electrical connection	
 of Industrial Ethernet interface 	15 pin Sub-D-socket (10Mbit/s AUI, 10/100 Mbit/s ITP)
• at the 1st interface / according to Industrial Ethernet	RJ45 port / AUI
design of the removable storage	
• C-PLUG	No
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage	5 V
relative symmetrical tolerance / at DC	
• at 5 V	5 %
consumed current	
 from backplane bus / at DC / at 5 V / typical 	1.4 A
power loss [W]	8.6 W
ambient conditions	
ambient temperature	
 during operation 	0 60 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-400 single width
width	25 mm
height	290 mm
depth	210 mm
net weight	0.7 kg
product features, product functions, product components / get	neral
number of units	
• per CPU / maximum	14

performance data / open communication	
number of possible connections / for open communication / by	64
means of SEND/RECEIVE blocks / maximum	
data volume	
 as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
 as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
 as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
 as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum 	2 Kibyte
performance data / S7 communication	
number of possible connections / for S7 communication	
• maximum	48
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	64
product functions / management, configuration, engineering	
product function / MIB support	No
protocol / is supported	
• SNMP v1	No
• LLDP	No
configuration software	
• required	STEP 7 V5.1 SP2 or higher
product functions / diagnostics	
product function / web-based diagnostics	No
product functions / switch	
product feature / switch	No
product functions / redundancy	
product function	
ring redundancy	No
product functions / security	
product function	
 password protection for Web applications 	No
ACL - IP-based	No
 ACL - IP-based for PLC/routing 	No
 switch-off of non-required services 	No
 blocking of communication via physical ports 	No
log file for unauthorized access	No
product functions / time	
product function / SICLOCK support	Yes
product function / pass on time synchronization	No
protocol / is supported	
• NTP	Yes
further information / internet-Links	
Internet-Link	
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
to website: Information and Download Center	http://www.siemens.com/industry/infocenter
to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection

	concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
last modified:	10/17/2022 🖸