



Figure similar

### MLFB-Ordering data

6SE6420-2AB21-5BA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Rated data                              |                          | General tech. specifications             |               |
|-----------------------------------------|--------------------------|------------------------------------------|---------------|
| <b>Input</b>                            |                          | <b>Power factor <math>\lambda</math></b> | 0.95          |
| <b>Number of phases</b>                 | 1 AC                     | <b>Efficiency <math>\eta</math></b>      | 0.96          |
| <b>Line voltage</b>                     | 200 ... 240 V $\pm 10$ % | <b>Ambient conditions</b>                |               |
| <b>Line frequency</b>                   | 47 ... 63 Hz             | <b>Cooling</b>                           | Fan           |
| <b>Rated current (HO)</b>               | 14.40 A                  | <b>Ambient temperature</b>               |               |
| <b>Output</b>                           |                          | <b>Operation (HO)</b>                    | -10 ... 50 °C |
| <b>Number of phases</b>                 | 3 AC                     | <b>Transport</b>                         | -40 ... 70 °C |
| <b>Rated voltage</b>                    | 240 V                    | <b>Storage</b>                           | -40 ... 70 °C |
| <b>Rated power (HO)</b>                 | 1.50 kW / 2.00 hp        |                                          |               |
| <b>Rated current (HO)</b>               | 7.40 A                   |                                          |               |
| <b>Pulse frequency</b>                  | 16000 Hz                 |                                          |               |
| <b>Output frequency for V/f control</b> | 0 ... 650 Hz             |                                          |               |

As a result of legal stipulations, a limit to 550 Hz is in production

### Overload capability

#### High Overload (HO)

150 % output current for 60 s, followed by 100 % output current for 240 s in a 300 s cycle time

MLFB-Ordering data                      6SE6420-2AB21-5BA1



Figure similar

| Mechanical data      |                     | Connections             |          |
|----------------------|---------------------|-------------------------|----------|
| Degree of protection | IP20 / UL open type | Motor end               |          |
| Frame size           | FSB                 | Conductor cross-section | 6.00 mm² |
| Net weight           | 3.30 kg             |                         |          |
| Width                | 149.0 mm            |                         |          |
| Height               | 202.0 mm            |                         |          |
| Depth                | 172.0 mm            |                         |          |

| Inputs / outputs        |   |
|-------------------------|---|
| Standard digital inputs |   |
| Number                  | 3 |
| Relay output            |   |
| Number                  | 1 |
| Analog inputs           |   |
| Number                  | 1 |
| Analog outputs          |   |
| Number                  | 1 |