

### MLFB-Ordering data

6SE6440-2UE24-0CA1



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Rated data                              |                          | General tech. specifications             |               |
|-----------------------------------------|--------------------------|------------------------------------------|---------------|
| <b>Input</b>                            |                          | <b>Power factor <math>\lambda</math></b> | 0.95          |
| <b>Number of phases</b>                 | 3 AC                     | <b>Efficiency <math>\eta</math></b>      | 0.96          |
| <b>Line voltage</b>                     | 500 ... 600 V $\pm 10$ % | <b>Ambient conditions</b>                |               |
| <b>Line frequency</b>                   | 47 ... 63 Hz             | <b>Cooling</b>                           | Fan           |
| <b>Rated current (LO)</b>               | 9.40 A                   | <b>Ambient temperature</b>               |               |
| <b>Rated current (HO)</b>               | 8.10 A                   | <b>Operation (LO)</b>                    | -10 ... 40 °C |
| <b>Output</b>                           |                          | <b>Operation (HO)</b>                    | -10 ... 50 °C |
| <b>Number of phases</b>                 | 3 AC                     | <b>Transport</b>                         | -40 ... 70 °C |
| <b>Rated voltage</b>                    | 600 V                    | <b>Storage</b>                           | -40 ... 70 °C |
| <b>Rated power (LO)</b>                 | 5.50 kW / 7.50 hp        |                                          |               |
| <b>Rated power (HO)</b>                 | 4.00 kW / 5.00 hp        |                                          |               |
| <b>Rated current (LO)</b>               | 9.00 A                   |                                          |               |
| <b>Rated current (HO)</b>               | 6.10 A                   |                                          |               |
| <b>Pulse frequency</b>                  | 4000 Hz                  |                                          |               |
| <b>Output frequency for V/f control</b> | 0 ... 650 Hz             |                                          |               |

As a result of legal stipulations, a limit to 550 Hz is in production

### Overload capability

#### Low Overload (LO)

140 % output current for 3 s, followed by 110 % output current for 57 s followed by 100 % output current for 240 s in a 300 s cycle time

#### High Overload (HO)

150 % output current for 60 s, followed by 100 % output current for 240 s in a 300 s cycle time

MLFB-Ordering data                      6SE6440-2UE24-0CA1



Figure similar

| Mechanical data      |                     | Connections             |           |
|----------------------|---------------------|-------------------------|-----------|
| Degree of protection | IP20 / UL open type | Motor end               |           |
| Frame size           | FSC                 | Conductor cross-section | 10.00 mm² |
| Net weight           | 5.50 kg             |                         |           |
| Width                | 185.0 mm            |                         |           |
| Height               | 245.0 mm            |                         |           |
| Depth                | 195.0 mm            |                         |           |

| Inputs / outputs        |   |
|-------------------------|---|
| Standard digital inputs |   |
| Number                  | 6 |
| Relay output            |   |
| Number                  | 3 |
| Analog inputs           |   |
| Number                  | 2 |
| Analog outputs          |   |
| Number                  | 2 |
| PTC/ KTY interface      |   |
| Number                  | 1 |