

Article No. :

6SL3210-1RH31-2UL0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :


| Rated data | | |
|-------------------------------------|---|------------------------------|
| Input | | |
| Number of phases | 3 AC | |
| Line voltage | 500 ... 690 V $\pm 10\%$ | |
| Line frequency | 47 ... 63 Hz | |
| Rated current (LO) | 111.00 A | |
| Rated current (HO) | 106.00 A | |
| Output | | |
| Number of phases | 3 AC | |
| Rated voltage | 690V IEC | 600V NEC¹⁾ |
| Rated power (LO) | 110.00 kW | 100.00 hp |
| Rated power (HO) | 90.00 kW | 100.00 hp |
| Rated current (LO) | 115.00 A | |
| Rated current (HO) | 100.00 A | |
| Max. output current | 156.00 A | |
| Pulse frequency | 2 kHz | |
| Output frequency for vector control | 0 ... 200 Hz | |
| Output frequency for V/f control | 0 ... 550 Hz | |
| Overload capability | | |
| Low Overload (LO) | 1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.35 x rated output current (i.e. 135 % overload) for 3 s with a cycle time of 300 s | |
| High Overload (HO) | 1.5 x output current rating (i.e., 150 % overload) for 60 s with a cycle time of 300 s | |

| General tech. specifications | |
|------------------------------|---------|
| Power factor λ | 0.90 |
| Offset factor $\cos \varphi$ | 0.99 |
| Efficiency η | 0.99 |
| Sound pressure level (1m) | 68 dB |
| Power loss | 1.95 kW |
| Filter class (integrated) | - |

| Ambient conditions | |
|--------------------------------|---|
| Cooling | Internal air cooling |
| Cooling air requirement | 0.153 m ³ /s (5.403 ft ³ /s) |
| Installation altitude | 1,000 m (3,280.84 ft) |
| Ambient temperature | |
| Operation LO | -20 ... 40 °C (-4 ... 104 °F) |
| Operation HO | -20 ... 50 °C (-4 ... 122 °F) |
| Transport | -40 ... 70 °C (-40 ... 158 °F) |
| Storage | -40 ... 70 °C (-40 ... 158 °F) |
| Relative humidity | |
| Max. operation | 95 % RH, condensation not permitted |
| Connections | |
| Line side | |
| Version | M10 bolt |
| Conductor cross-section | 35.00 ... 120.00 mm ² (AWG 2 ... AWG -3) |
| Motor end | |
| Version | M10 bolt |
| Conductor cross-section | 35.00 ... 120.00 mm ² (AWG 2 ... AWG -3) |
| Max. motor cable length | |
| Shielded | 300 m (984.25 ft) |
| Unshielded | 450 m (1,476.38 ft) |
| Mechanical data | |
| Degree of protection | IP20 / UL open type |
| Frame size | FSF |
| Net weight | 60.00 kg (132.28 lb) |
| Dimensions | |
| Width | 305 mm (12.01 in) |
| Height | 708 mm (27.87 in) |
| Depth | 357 mm (14.06 in) |
| Standards | |
| Compliance with standards | UL, cUL, CE, SEMI F47 |
| CE marking | Low-voltage directive 2006/95/EC |

Article No. : 6SL3210-1RH31-2UL0

| Converter losses to IEC61800-9-2* | |
|--|---------|
| Efficiency class | IE2 |
| Comparison with the reference converter (90% / 100%) | 34.40 % |



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard IEC61800-9-2) of the relative torque generating current (I) over the relative motor stator frequency (f). The values are valid for the basic version of the converter without options/components.

*converted values

¹⁾The output current and HP ratings are valid for the voltage range 550V-600V