



Figure similar

MLFB-Ordering data

6SL3210-5FE10-8UF0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Rated data              |                           | Ambient conditions         |                                  |
|-------------------------|---------------------------|----------------------------|----------------------------------|
| <b>Input</b>            |                           | <b>Cooling</b>             | natural convection               |
| Number of phases        | 3 AC                      | Installation altitude      | 1000 m                           |
| Line voltage            | 380 ... 480 V +10 % -15 % | <b>Ambient temperature</b> |                                  |
| Line frequency          | 45 ... 66 Hz              | Operation                  | 0 ... 45 °C                      |
| <b>Output</b>           |                           | Storage                    | -40 ... 70 °C                    |
| Rated power             | 0.75 kW                   | <b>Relative humidity</b>   |                                  |
| Rated current (IN)      | 2.10 A                    | Max. operation             | 90 %                             |
| Max. output current     | 6.30 A                    | <b>Standards</b>           |                                  |
| <b>Inputs / outputs</b> |                           | Compliance with standards  | CE, KC, cULus, EAC, C-Tick (RCM) |

### Standard digital inputs

|        |   |
|--------|---|
| Number | 4 |
|--------|---|

### Digital outputs

|        |   |
|--------|---|
| Number | 2 |
|--------|---|

| Mechanical data      |                     |
|----------------------|---------------------|
| Degree of protection | IP20 / UL open type |
| Frame size           | FSA                 |
| Net weight           | 1.85 kg             |
| Width                | 80.0 mm             |
| Height               | 180.0 mm            |
| Depth                | 200.0 mm            |