SIEMENS

Data sheet for SINAMICS Power module PM240-2

Article No.: 6SL3210-1PH26-2AL0

Client order no. : Order no. : Offer no. : Remarks :





Figure simil

Rated data		
Input		
Number of phases	3 AC	
Line voltage	500 690 V ±10 %	
Line frequency	47 63 Hz	
Rated current (LO)	59.00 A	
Rated current (HO)	54.00 A	
Output		
Number of phases	3 AC	
Rated voltage	690V IEC	600V NEC 1)
Rated power (LO)	55.00 kW	60.00 hp
Rated power (HO)	45.00 kW	50.00 hp
Rated current (LO)	62.00 A	
Rated current (HO)	52.00 A	
Max. output current	104.00 A	
Pulse frequency	2 kHz	
Output frequency for vector control	0 200 Hz	
Output frequency for V/f control	0 550 Hz	
Overload capability		

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 \times rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

 $1.5\times$ output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 \times output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

General tech. specifications		
Power factor λ	0.90	
Offset factor $\cos\phi$	0.99	
Efficiency η	0.98	
Sound pressure level (1m)	71 dB	
Power loss	1.22 kW	
Filter class (integrated)	Class A	


Ambient	conditions	
Cooling	Internal air cooling	
Cooling air requirement	0.083 m³/s (2.931 ft³/s)	
Installation altitude	1,000 m (3,280.84 ft)	
Ambient temperature	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Operation LO	-20 40 °C (-4 104 °F)	
Operation HO	-20 50 °C (-4 122 °F)	
Transport	-40 70 °C (-40 158 °F)	
Storage	-40 70 °C (-40 158 °F)	
Relative humidity	10 70 C(10 130 1)	
Max. operation	95 % RH, condensation not permitted	
•	· ·	
Connections		
Line side		
Version	screw-type terminal	
Conductor cross-section	25.00 70.00 mm ² (AWG 4 AWG -1)	
Motor end		
Version	Screw-type terminals	
Conductor cross-section	25.00 70.00 mm ² (AWG 4 AWG -1)	
DC link (for braking resistor)		
Version	Screw-type terminals	
Conductor cross-section	10.00 35.00 mm ² (AWG 8 AWG 2)	
Cable length	10 m (32.81 ft)	
PE connection	Screw-type terminals	
Max. motor cable length		
Shielded	200 m (656.17 ft)	
Unshielded	300 m (984.25 ft)	
Mechar	nical data	
Degree of protection	IP20 / UL open type	
Frame size	FSE	
Net weight	28.00 kg (61.73 lb)	
Dimensions		
Width	275 mm (10.83 in)	
Height	551 mm (21.69 in)	
Depth	237 mm (9.33 in)	
Standards		
Compliance with standards	UL, cUL, CE, C-Tick (RCM), SEMI F47	
Compliance with standards	OL, COL, CL, C TICK (NCIVI), SEIVITT 47	



Data sheet for SINAMICS Power module PM240-2

Article No.: 6SL3210-1PH26-2AL0

Converter losses to IEC61800-9-2*		
Efficiency class	IE2	
Comparison with the reference converter (90% / 100%)	39.20 %	



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard IEC61800-9-2) of the relative torque generating current (I) over the relative motor stator frequency (f). The values are valid for the basic version of the converter without options/components.

*converted values

¹⁾ The output current and HP ratings are valid for the voltage range 550V-600V