

MLFB-Ordering data

6SL3211-0AB11-2BA1



Figure similar

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data		Ambient conditions	
Input		Installation altitude	
Number of phases	1 AC	Operation	1000 m
Line voltage	200 ... 240 V ±10 %	Storage	-10 ... 40 °C
Line frequency	47 ... 63 Hz	Relative humidity	
Rated current	2.30 A	Max. operation	-40 ... 70 °C
Output		95 % condensation not permitted	
Number of phases	3 AC	Closed-loop control techniques	
Rated power	0.12 kW	V/f linear / square-law / parameterizable	
Rated current (IN)	0.90 A	Yes	
Pulse frequency	8 kHz	Standards	
Output frequency for V/f control	0 ... 650 Hz	Compliance with standards	UL, cUL, CE, C-Tick (RCM)
As a result of legal stipulations, a limit to 550 Hz is in production		CE marking	Low-voltage directive 2006/95/EC
General tech. specifications		Inputs / outputs	
Offset factor cos φ	0.95	Digital inputs	
Communication		Number	3
Communication	RS485	Analog inputs	
Mechanical data		Number	1 (Analog variant, for setpoint (0...10 V, can be scaled or used as 4th digital input))
Degree of protection	IP20 / UL open type	Digital outputs	
Frame size	FSA	Number	1 (Isolated optocoupler output, NPN type)
Net weight	0.80 kg		
Width	90.0 mm		
Height	150.0 mm		
Depth	116.0 mm		