



power contactor, AC-3, 35 A, 18.5 kW / 400 V, 4-pole, 20-33 V AC/DC, 50/60 Hz, with integrated varistor, main contacts: 2 NO + 2 NC, auxiliary contacts: 1 NO + 1 NC, screw terminal, size: S2

| | |
|--|--|
| product brand name | SIRIUS |
| product designation | contactor |
| product type designation | 3RT25 |
| General technical data | |
| size of contactor | S2 |
| product extension | |
| • function module for communication | No |
| • auxiliary switch | Yes |
| power loss [W] for rated value of the current | |
| • at AC in hot operating state per pole | 2.2 W |
| • without load current share typical | 2.4 W |
| type of calculation of power loss depending on pole | quadratic |
| insulation voltage | |
| • of main circuit with degree of pollution 3 rated value | 690 V |
| • of auxiliary circuit with degree of pollution 3 rated value | 690 V |
| surge voltage resistance | |
| • of main circuit rated value | 6 kV |
| • of auxiliary circuit rated value | 6 kV |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 400 V |
| shock resistance at rectangular impulse | |
| • at AC | 7.7g / 5 ms, 4.5g / 10 ms |
| • at DC | 7.7g / 5 ms, 4.5g / 10 ms |
| shock resistance with sine pulse | |
| • at AC | 12g / 5 ms, 7g / 10 ms |
| • at DC | 12g / 5 ms, 7g / 10 ms |
| mechanical service life (operating cycles) | |
| • of contactor typical | 10 000 000 |
| • of the contactor with added electronically optimized auxiliary switch block typical | 5 000 000 |
| • of the contactor with added auxiliary switch block typical | 10 000 000 |
| reference code according to IEC 81346-2 | Q |
| Substance Prohibitance (Date) | 10/01/2014 |
| SVHC substance name | Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 |
| Weight | 1.192 kg |
| Ambient conditions | |
| installation altitude at height above sea level maximum | 2 000 m |
| ambient temperature | |
| • during operation | -40 ... +70 °C |
| • during storage | -55 ... +80 °C |

| | |
|---|---|
| relative humidity minimum | 10 % |
| relative humidity at 55 °C according to IEC 60068-2-30 maximum | 95 % |
| Main circuit | |
| number of poles for main current circuit | 4 |
| number of NO contacts for main contacts | 2 |
| number of NC contacts for main contacts | 2 |
| operational current | |
| • at AC-1 up to 690 V | |
| — at ambient temperature 40 °C rated value | 60 A |
| — at ambient temperature 60 °C rated value | 55 A |
| • at AC-2 at AC-3 at 400 V | |
| — per NO contact rated value | 35 A |
| — per NC contact rated value | 35 A |
| minimum cross-section in main circuit at maximum AC-1 rated value | 16 mm ² |
| operational current | |
| • at 1 current path at DC-1 | |
| — at 24 V rated value | 55 A |
| — at 110 V rated value | 4.5 A |
| — at 220 V rated value | 1 A |
| — at 440 V rated value | 0.4 A |
| • with 2 current paths in series at DC-1 | |
| — at 24 V rated value | 55 A |
| — at 110 V rated value | 45 A |
| — at 220 V rated value | 5 A |
| — at 440 V rated value | 1 A |
| • at 1 current path at DC-3 at DC-5 | |
| — at 24 V per NC contact rated value | 35 A |
| — at 24 V per NO contact rated value | 35 A |
| — at 110 V per NC contact rated value | 1.25 A |
| — at 110 V per NO contact rated value | 2.5 A |
| — at 220 V per NC contact rated value | 0.5 A |
| — at 220 V per NO contact rated value | 1 A |
| — at 440 V per NC contact rated value | 0.045 A |
| — at 440 V per NO contact rated value | 0.1 A |
| • with 2 current paths in series at DC-3 at DC-5 | |
| — at 24 V per NC contact rated value | 55 A |
| — at 24 V per NO contact rated value | 55 A |
| — at 110 V per NC contact rated value | 12.5 A |
| — at 110 V per NO contact rated value | 25 A |
| — at 220 V per NC contact rated value | 2.5 A |
| — at 220 V per NO contact rated value | 5 A |
| — at 440 V per NC contact rated value | 0.135 A |
| — at 440 V per NO contact rated value | 0.27 A |
| operating power at AC-2 at AC-3 | |
| • at 230 V per NC contact rated value | 11 kW |
| • at 230 V per NO contact rated value | 11 kW |
| • at 400 V per NC contact rated value | 18.5 kW |
| • at 400 V per NO contact rated value | 18.5 kW |
| short-time withstand current in cold operating state up to 40 °C | |
| • limited to 1 s switching at zero current maximum | 546 A; Use minimum cross-section acc. to AC-1 rated value |
| • limited to 5 s switching at zero current maximum | 443 A; Use minimum cross-section acc. to AC-1 rated value |
| • limited to 10 s switching at zero current maximum | 334 A; Use minimum cross-section acc. to AC-1 rated value |
| • limited to 30 s switching at zero current maximum | 241 A; Use minimum cross-section acc. to AC-1 rated value |
| • limited to 60 s switching at zero current maximum | 196 A; Use minimum cross-section acc. to AC-1 rated value |
| power loss [W] at AC-3 at 400 V for rated value of the operational current per conductor | 2.2 W |
| power loss [W] at AC-3e at 400 V for rated value of the operational current per conductor | 2.2 W |
| no-load switching frequency | |

| | |
|---|---------------|
| • at AC | 500 1/h |
| • at DC | 500 1/h |
| operating frequency | |
| • at AC-1 maximum | 350 1/h |
| Control circuit/ Control | |
| type of voltage of the control supply voltage | AC/DC |
| control supply voltage at AC | |
| • at 50 Hz rated value | 20 ... 33 V |
| • at 60 Hz rated value | 20 ... 33 V |
| control supply voltage at DC rated value | 20 ... 33 V |
| operating range factor control supply voltage rated value of magnet coil at DC | |
| • initial value | 0.8 |
| • full-scale value | 1.1 |
| operating range factor control supply voltage rated value of magnet coil at AC | |
| • at 50 Hz | 0.8 ... 1.1 |
| • at 60 Hz | 0.8 ... 1.1 |
| design of the surge suppressor | with varistor |
| inrush current peak | 30 A |
| duration of inrush current peak | 30 µs |
| locked-rotor current mean value | 6.5 A |
| locked-rotor current peak | 12 A |
| duration of locked-rotor current | 230 ms |
| holding current mean value | 105 mA |
| apparent pick-up power of magnet coil at AC | 110 VA |
| • at 50 Hz | 110 VA |
| • at 60 Hz | 110 VA |
| inductive power factor with closing power of the coil | 0.95 |
| • at 50 Hz | 0.95 |
| • at 60 Hz | 0.95 |
| apparent holding power of magnet coil at AC | 2.5 VA |
| • at 50 Hz | 2.5 VA |
| • at 60 Hz | 2.5 VA |
| inductive power factor with the holding power of the coil | 0.95 |
| • at 50 Hz | 0.95 |
| • at 60 Hz | 0.95 |
| closing power of magnet coil at DC | 70 W |
| holding power of magnet coil at DC | 1.5 W |
| closing delay | |
| • at AC | 30 ... 110 ms |
| • at DC | 30 ... 110 ms |
| opening delay | |
| • at AC | 30 ... 55 ms |
| • at DC | 30 ... 55 ms |
| arcing time | 10 ... 20 ms |
| control version of the switch operating mechanism | UC |
| residual current of the electronics for control with signal <0> | |
| • at AC at 230 V maximum permissible | 20 A |
| • at DC at 24 V maximum permissible | 20 A |
| Auxiliary circuit | |
| number of NC contacts for auxiliary contacts instantaneous contact | 1 |
| number of NO contacts for auxiliary contacts instantaneous contact | 1 |
| operational current at AC-12 maximum | 10 A |
| operational current at AC-15 | |
| • at 230 V rated value | 6 A |
| • at 400 V rated value | 3 A |
| • at 500 V rated value | 2 A |
| • at 690 V rated value | 1 A |

| | |
|---|--|
| operational current at DC-12 | |
| • at 24 V rated value | 10 A |
| • at 48 V rated value | 6 A |
| • at 60 V rated value | 6 A |
| • at 110 V rated value | 3 A |
| • at 125 V rated value | 2 A |
| • at 220 V rated value | 1 A |
| • at 600 V rated value | 0.15 A |
| operational current at DC-13 | |
| • at 24 V rated value | 10 A |
| • at 48 V rated value | 2 A |
| • at 60 V rated value | 2 A |
| • at 110 V rated value | 1 A |
| • at 125 V rated value | 0.9 A |
| • at 220 V rated value | 0.3 A |
| • at 600 V rated value | 0.1 A |
| contact reliability of auxiliary contacts | 1 faulty switching per 100 million (17 V, 1 mA) |
| UL/CSA ratings | |
| yielded mechanical performance [hp] | |
| • for 3-phase AC motor at 460/480 V rated value | 20 hp |
| contact rating of auxiliary contacts according to UL | A600 / P600 |
| Short-circuit protection | |
| design of the fuse link | |
| • for short-circuit protection of the main circuit | |
| — with type of coordination 1 required | gG: 125 A (690 V, 100 kA) |
| — with type of assignment 2 required | gG: 63A (690V, 100kA) |
| • for short-circuit protection of the auxiliary switch required | fuse gG: 10 A |
| Installation/ mounting/ dimensions | |
| mounting position | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| fastening method side-by-side mounting | Yes |
| fastening method | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 50022 |
| height | 114 mm |
| width | 75 mm |
| depth | 130 mm |
| required spacing | |
| • with side-by-side mounting | |
| — forwards | 0 mm |
| — backwards | 0 mm |
| — upwards | 0 mm |
| — downwards | 0 mm |
| — at the side | 0 mm |
| • for grounded parts | |
| — forwards | 0 mm |
| — backwards | 0 mm |
| — upwards | 50 mm |
| — at the side | 10 mm |
| — downwards | 50 mm |
| • for live parts | |
| — forwards | 0 mm |
| — backwards | 0 mm |
| — upwards | 50 mm |
| — downwards | 50 mm |
| — at the side | 10 mm |
| Connections/ Terminals | |
| type of electrical connection | |
| • for main current circuit | screw-type terminals |
| • for auxiliary and control circuit | screw-type terminals |
| • at contactor for auxiliary contacts | Screw-type terminals |
| • of magnet coil | Screw-type terminals |
| type of connectable conductor cross-sections for main contacts | |

| | |
|---|---|
| • solid | 2x (1 ... 35 mm ²), 1x (1 ... 50 mm ²) |
| • solid or stranded | 2x (1 ... 35 mm ²), 1x (1 ... 50 mm ²) |
| • finely stranded with core end processing | 2x (1 ... 25 mm ²), 1x (1 ... 35 mm ²) |
| type of connectable conductor cross-sections | |
| • for auxiliary contacts | |
| — solid | 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²) |
| — solid or stranded | 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²) |
| — finely stranded with core end processing | 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²) |
| • for AWG cables for auxiliary contacts | 2x (20 ... 16), 2x (18 ... 14) |
| AWG number as coded connectable conductor cross section for main contacts | 18 ... 1 |

Safety related data

| | |
|--|--|
| product function | |
| • mirror contact according to IEC 60947-4-1 | Yes |
| • positively driven operation according to IEC 60947-5-1 | No |
| Electrical Safety | |
| protection class IP on the front according to IEC 60529 | IP20 |
| touch protection on the front according to IEC 60529 | finger-safe, for vertical contact from the front |

Approvals Certificates

| | |
|---|---|
| General Product Approval | |
|  |  |
| | Confirmation |
| |  |
| |  |
| | KC |

| General Product Approval | EMV | Test Certificates | Marine / Shipping |
|---|---|--|--|
|  |  | Special Test Certificate | Type Test Certificates/Test Report |
| | | |  ABS |
| | | |  BUREAU VERITAS |

| | |
|---|------------------------------|
| Marine / Shipping | other |
|  | Confirmation |
|  | |
|  | |
|  | |
|  | |

| Railway | Dangerous goods | Environment |
|--|---------------------------------------|---|
| Special Test Certificate | Transport Information | Environmental Confirmations |

| |
|--|
| Further information |
| Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 |
| Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10 |
| Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2535-1NB30 |
| Cax online generator http://support.automation.siemens.com/WW/CAxorder/default.aspx?lang=en&mlfb=3RT2535-1NB30 |
| Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3RT2535-1NB30 |
| Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2535-1NB30&lang=en |
| Characteristic: Tripping characteristics, I ² t, Let-through current https://support.industry.siemens.com/cs/ww/en/ps/3RT2535-1NB30/char |
| Further characteristics (e.g. electrical endurance, switching frequency) |



