



Figure similar

SITOR fuse link, with slotted blade contacts, NH3, In: 450 A, aR, Un AC: 1500 V, Un DC: 900 V, front indicator

Model			
product brand name	SETRON		
product designation	SITOR fuse link		
design of the product	With slotted blade contacts		
design of an identification indicator	front indicator		
design of the switching contact	with slotted blade contacts for M10 screw fixing. mounting dimension: 170 mm		
design of the fuse link	SITOR, LV HRC design		
General technical data			
size of fuse system according to EN 60269-1	NH3		
operating class of the fuse link	aR		
varying load factor (WL)	1		
type of voltage of the operating voltage	AC/DC		
operating voltage at AC according to UL rated value	1 500 V		
Supply voltage			
supply voltage			
• at AC	1 500 V		
• at DC	900 V		
Breaking Capacity			
switching capacity current			
• according to IEC 60947-2 rated value	100 kA		
Dissipation			
power loss [W]	160 W		
power loss [W]			
• for rated value of the current at AC in hot operating state per pole	160 W		
• maximum	160 W		
Product details			
product description	with blade contacts, silver-plated		
accessories included	no		
Mechanical Design			
mounting position	Any, preferably vertical		
net weight	1 595 g		
Environmental conditions			
ambient temperature during operation			
• minimum	-20 °C		
• maximum	50 °C		
environmental category	-20 to +50 at 95% relative humidity		
Approvals Certificates			
General Product Approval		Test Certificates	other



[Confirmation](#)



[Special Test Certificate](#)

[Miscellaneous](#)

other	Environment
-------	-------------

[Confirmation](#)

[Miscellaneous](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE5633-0C>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NE5633-0C>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE5633-0C

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



