



| | |
|--|---|
| product brand name | SIRIUS |
| product category | Hybrid switching devices |
| product designation | Soft starter |
| product type designation | 3RW52 |
| manufacturer's article number | <ul style="list-style-type: none"> of standard HMI module usable of high feature HMI module usable of communication module PROFINET standard usable of communication module PROFIBUS usable of communication module Modbus TCP usable of communication module Modbus RTU usable of communication module Ethernet/IP of circuit breaker usable at 400 V of circuit breaker usable at 500 V of circuit breaker usable at 400 V at inside-delta circuit of circuit breaker usable at 500 V at inside-delta circuit of the gG fuse usable up to 690 V of the gG fuse usable at inside-delta circuit up to 500 V of full range R fuse link for semiconductor protection usable up to 690 V of back-up R fuse link for semiconductor protection usable up to 690 V |
| | 3RW5980-0HS00 3RW5980-0HF00 3RW5980-0CS00 3RW5980-0CP00 3RW5980-0CT00 3RW5980-0CR00 3RW5980-0CE00 3VA2110-7MN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10 3VA2110-7MN32-0AA0; Type of coordination 1, Iq = 20 kA, CLASS 10 3VA2216-7MN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10 3VA2216-7MN32-0AA0; Type of coordination 1, Iq = 20 kA, CLASS 10 3NA3132-6; Type of coordination 1, Iq = 65 kA 3NA3132-6; Type of coordination 1, Iq = 65 kA 3NE1224-0; Type of coordination 2, Iq = 65 kA 3NE8024-1; Type of coordination 2, Iq = 65 kA |
| General technical data | |
| starting voltage [%] | 30 ... 100 % |
| stopping voltage [%] | 50 %; non-adjustable |
| start-up ramp time of soft starter | 0 ... 20 s |
| current limiting value [%] adjustable | 130 ... 700 % |
| certificate of suitability | <ul style="list-style-type: none"> CE marking UL approval CSA approval |
| | Yes Yes Yes |
| product component | <ul style="list-style-type: none"> HMI-High Feature is supported HMI-Standard is supported HMI-High Feature |
| | No Yes Yes |
| product feature integrated bypass contact system | Yes |
| number of controlled phases | 3 |
| buffering time in the event of power failure | |

| | |
|---|---|
| • for main current circuit | 100 ms |
| • for control circuit | 100 ms |
| insulation voltage rated value | 600 V |
| degree of pollution | 3, acc. to IEC 60947-4-2 |
| impulse voltage rated value | 6 kV |
| blocking voltage of the thyristor maximum | 1 400 V |
| service factor | 1 |
| surge voltage resistance rated value | 6 kV |
| maximum permissible voltage for protective separation | |
| • between main and auxiliary circuit | 600 V |
| shock resistance | 15 g / 11 ms, from 12 g / 11 ms with potential contact lifting |
| vibration resistance | 15 mm to 6 Hz; 2g to 500 Hz |
| utilization category according to IEC 60947-4-2 | AC 53a |
| reference code according to IEC 81346-2 | Q |
| Substance Prohibitance (Date) | 02/15/2018 |
| SVHC substance name | Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one - 71868-10-5 Dibutylbis(pentane-2,4-dionato-O,O')tin - 22673-19-4 |
| Weight | 6.46 kg |
| product function | |
| • ramp-up (soft starting) | Yes |
| • ramp-down (soft stop) | Yes |
| • Soft Torque | Yes |
| • adjustable current limitation | Yes |
| • pump ramp down | Yes |
| • intrinsic device protection | Yes |
| • motor overload protection | Yes; Electronic motor overload protection |
| • evaluation of thermistor motor protection | No |
| • inside-delta circuit | Yes |
| • auto-RESET | Yes |
| • manual RESET | Yes |
| • remote reset | Yes; By turning off the control supply voltage |
| • communication function | Yes |
| • operating measured value display | Yes; Only in conjunction with special accessories |
| • error logbook | Yes; Only in conjunction with special accessories |
| • via software parameterizable | No |
| • via software configurable | Yes |
| • PROFlenergy | Yes; in connection with the PROFINET Standard communication module |
| • firmware update | Yes |
| • removable terminal for control circuit | Yes |
| • torque control | No |
| • analog output | Yes; 4 ... 20 mA (default) / 0 ... 10 V (parameterizable with High Feature HMI) |
| Power Electronics | |
| operational current | |
| • at 40 °C rated value | 77 A |
| • at 50 °C rated value | 68 A |
| • at 60 °C rated value | 62 A |
| operational current at inside-delta circuit | |
| • at 40 °C rated value | 133 A |
| • at 50 °C rated value | 118 A |
| • at 60 °C rated value | 107 A |
| operating voltage | |
| • rated value | 200 ... 480 V |
| • at inside-delta circuit rated value | 200 ... 480 V |
| relative negative tolerance of the operating voltage | -15 % |
| relative positive tolerance of the operating voltage | 10 % |
| relative negative tolerance of the operating voltage at inside-delta circuit | -15 % |
| relative positive tolerance of the operating voltage at inside-delta circuit | 10 % |
| operating power for 3-phase motors | |

| | |
|--|---|
| • at 230 V at 40 °C rated value | 22 kW |
| • at 230 V at inside-delta circuit at 40 °C rated value | 37 kW |
| • at 400 V at 40 °C rated value | 37 kW |
| • at 400 V at inside-delta circuit at 40 °C rated value | 75 kW |
| Operating frequency 1 rated value | 50 Hz |
| Operating frequency 2 rated value | 60 Hz |
| relative negative tolerance of the operating frequency | -10 % |
| relative positive tolerance of the operating frequency | 10 % |
| adjustable motor current | |
| • at rotary coding switch on switch position 1 | 32 A |
| • at rotary coding switch on switch position 2 | 35 A |
| • at rotary coding switch on switch position 3 | 38 A |
| • at rotary coding switch on switch position 4 | 41 A |
| • at rotary coding switch on switch position 5 | 44 A |
| • at rotary coding switch on switch position 6 | 47 A |
| • at rotary coding switch on switch position 7 | 50 A |
| • at rotary coding switch on switch position 8 | 53 A |
| • at rotary coding switch on switch position 9 | 56 A |
| • at rotary coding switch on switch position 10 | 59 A |
| • at rotary coding switch on switch position 11 | 62 A |
| • at rotary coding switch on switch position 12 | 65 A |
| • at rotary coding switch on switch position 13 | 68 A |
| • at rotary coding switch on switch position 14 | 71 A |
| • at rotary coding switch on switch position 15 | 74 A |
| • at rotary coding switch on switch position 16 | 77 A |
| • minimum | 32 A |
| adjustable motor current | |
| • for inside-delta circuit at rotary coding switch on switch position 1 | 55.4 A |
| • for inside-delta circuit at rotary coding switch on switch position 2 | 60.6 A |
| • for inside-delta circuit at rotary coding switch on switch position 3 | 65.8 A |
| • for inside-delta circuit at rotary coding switch on switch position 4 | 71 A |
| • for inside-delta circuit at rotary coding switch on switch position 5 | 76.2 A |
| • for inside-delta circuit at rotary coding switch on switch position 6 | 81.4 A |
| • for inside-delta circuit at rotary coding switch on switch position 7 | 86.6 A |
| • for inside-delta circuit at rotary coding switch on switch position 8 | 91.8 A |
| • for inside-delta circuit at rotary coding switch on switch position 9 | 97 A |
| • for inside-delta circuit at rotary coding switch on switch position 10 | 102 A |
| • for inside-delta circuit at rotary coding switch on switch position 11 | 107 A |
| • for inside-delta circuit at rotary coding switch on switch position 12 | 113 A |
| • for inside-delta circuit at rotary coding switch on switch position 13 | 118 A |
| • for inside-delta circuit at rotary coding switch on switch position 14 | 123 A |
| • for inside-delta circuit at rotary coding switch on switch position 15 | 128 A |
| • for inside-delta circuit at rotary coding switch on switch position 16 | 133 A |
| • at inside-delta circuit minimum | 55.4 A |
| minimum load [%] | 15 %; Relative to smallest settable I_e |
| power loss [W] for rated value of the current at AC | |
| • at 40 °C after startup | 35 W |
| • at 50 °C after startup | 32 W |
| • at 60 °C after startup | 31 W |
| power loss [W] at AC at current limitation 350 % | |

| | |
|--|--|
| • at 40 °C during startup | 1 107 W |
| • at 50 °C during startup | 933 W |
| • at 60 °C during startup | 826 W |
| Control circuit/ Control | |
| type of voltage of the control supply voltage | AC |
| control supply voltage at AC | |
| • at 50 Hz | 110 ... 250 V |
| • at 60 Hz | 110 ... 250 V |
| relative negative tolerance of the control supply voltage at AC at 50 Hz | -15 % |
| relative positive tolerance of the control supply voltage at AC at 50 Hz | 10 % |
| relative negative tolerance of the control supply voltage at AC at 60 Hz | -15 % |
| relative positive tolerance of the control supply voltage at AC at 60 Hz | 10 % |
| control supply voltage frequency | 50 ... 60 Hz |
| relative negative tolerance of the control supply voltage frequency | -10 % |
| relative positive tolerance of the control supply voltage frequency | 10 % |
| control supply current in standby mode rated value | 30 mA |
| holding current in bypass operation rated value | 75 mA |
| inrush current by closing the bypass contacts maximum | 2.5 A |
| inrush current peak at application of control supply voltage maximum | 12.2 A |
| duration of inrush current peak at application of control supply voltage | 2.2 ms |
| design of the overvoltage protection | Varistor |
| design of short-circuit protection for control circuit | 4 A gG fuse (Icu=1 kA), 6 A quick-acting fuse (Icu=1 kA), C1 miniature circuit breaker (Icu= 600 A), C6 miniature circuit breaker (Icu= 300 A); Is not part of scope of supply |
| Inputs/ Outputs | |
| number of digital inputs | 1 |
| number of digital outputs | 3 |
| • not parameterizable | 2 |
| digital output version | 2 normally-open contacts (NO) / 1 changeover contact (CO) |
| number of analog outputs | 1 |
| switching capacity current of the relay outputs | |
| • at AC-15 at 250 V rated value | 3 A |
| • at DC-13 at 24 V rated value | 1 A |
| Installation/ mounting/ dimensions | |
| mounting position | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back |
| fastening method | screw fixing |
| height | 306 mm |
| width | 185 mm |
| depth | 203 mm |
| required spacing with side-by-side mounting | |
| • forwards | 10 mm |
| • backwards | 0 mm |
| • upwards | 100 mm |
| • downwards | 75 mm |
| • at the side | 5 mm |
| weight without packaging | 5.6 kg |
| Connections/ Terminals | |
| type of electrical connection | |
| • for main current circuit | box terminal |
| • for control circuit | spring-loaded terminals |
| width of connection bar maximum | 25 mm |
| type of connectable conductor cross-sections for main contacts for box terminal | |
| • using the front clamping point solid | 1x (2.5 ... 16 mm ²) |
| • using the front clamping point finely stranded with core | 1x (2.5 ... 50 mm ²) |

| | |
|--|--|
| end processing | 1x (10 ... 70 mm ²) 1x (2.5 ... 16 mm ²) 1x (10 ... 2/0) 2x (2.5 ... 16 mm ²) 2x (2.5 ... 35 mm ²) 2x (6 ... 16 mm ²), 2x (10 ... 50 mm ²) 1x (2.5 ... 50 mm ²) 1x (10 ... 70 mm ²) |
| type of connectable conductor cross-sections | 2x (0.25 ... 1.5 mm ²) 2x (0.25 ... 1.5 mm ²) 2x (24 ... 16) 2x (24 ... 16) |
| wire length | 800 m 100 m |
| tightening torque | 4.5 ... 6 N·m 0.8 ... 1.2 N·m |
| tightening torque [lbf·in] | 40 ... 53 lbf·in 7 ... 10.3 lbf·in |
| Ambient conditions | |
| installation altitude at height above sea level maximum | 5 000 m; Derating as of 1000 m, see catalog |
| ambient temperature | -25 ... +60 °C; Please observe derating at temperatures of 40 °C or above -40 ... +80 °C |
| environmental category | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6 1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m) |
| Environmental footprint | |
| Global Warming Potential [CO ₂ eq] total | 296 kg |
| Global Warming Potential [CO ₂ eq] during manufacturing | 67.7 kg |
| global warming potential [CO ₂ eq] during sales | 1.84 kg |
| Global Warming Potential [CO ₂ eq] during operation | 242 kg |
| Global Warming Potential [CO ₂ eq] after end of life | -15.7 kg |
| Siemens Eco Profile (SEP) | Siemens EcoTech |
| Electromagnetic compatibility | |
| EMC emitted interference | acc. to IEC 60947-4-2: Class A |
| Communication/ Protocol | |
| communication module is supported | Yes |
| • PROFINET standard | Yes |
| • EtherNet/IP | Yes |
| • Modbus RTU | Yes |
| • Modbus TCP | Yes |
| • PROFIBUS | Yes |
| UL/CSA ratings | |
| manufacturer's article number | |
| • of circuit breaker usable for Standard Faults | |
| — at 460/480 V according to UL | Siemens type: 3VA51, max. 125 A; I _q = 10 kA |
| — 60/480 V according to UL | Siemens type: 3VA51, max. 125 A; I _q max = 65 kA |
| — at 460/480 V at inside-delta circuit according to UL | Siemens type: 3VA51, max. 125 A; I _q = 10 kA |
| — 60/480 V at inside-delta circuit according to UL | Siemens type: 3VA51, max. 125 A; I _q max = 65 kA |

| | |
|--|---|
| — at 575/600 V according to UL | Siemens type: 3VA51, max. 125 A; Iq = 10 kA |
| — at 575/600 V at inside-delta circuit according to UL | Siemens type: 3VA51, max. 125 A; Iq = 10 kA |
| • of the fuse | |
| — usable for Standard Faults up to 575/600 V according to UL | Type: Class RK5 / K5, max. 250 A; Iq = 10 kA |
| — usable for High Faults up to 575/600 V according to UL | Type: Class J / L, max. 250 A; Iq = 100 kA |
| — usable for Standard Faults at inside-delta circuit up to 575/600 V according to UL | Type: Class RK5 / K5, max. 250 A; Iq = 10 kA |
| — usable for High Faults at inside-delta circuit up to 575/600 V according to UL | Type: Class J / L, max. 250 A; Iq = 100 kA |
| operating power [hp] for 3-phase motors | |
| • at 200/208 V at 50 °C rated value | 20 hp |
| • at 220/230 V at 50 °C rated value | 25 hp |
| • at 460/480 V at 50 °C rated value | 50 hp |
| • at 200/208 V at inside-delta circuit at 50 °C rated value | 30 hp |
| • at 220/230 V at inside-delta circuit at 50 °C rated value | 40 hp |
| • at 460/480 V at inside-delta circuit at 50 °C rated value | 75 hp |
| contact rating of auxiliary contacts according to UL | R300-B300 |
| Electrical Safety | |
| protection class IP on the front according to IEC 60529 | IP00; IP20 with cover |
| touch protection on the front according to IEC 60529 | finger-safe, for vertical contact from the front with cover |

Approvals Certificates

General Product Approval



[Confirmation](#)



| EMV | Test Certificates | Marine / Shipping |
|-----------------------------------|------------------------------|--|
| | KC | Type Test Certificates/Test Report |
| | | |
| Marine / Shipping | other | Environment |
| | Confirmation | Environmental Confirmations |

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5226-3AC14>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5226-3AC14>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5226-3AC14>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5226-3AC14&lang=en

Characteristic: Tripping characteristics, I_{pt}, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5226-3AC14/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5226-3AC14&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>



