

## Data sheet

## 6GK5992-1AK00-8AA0

### product type designation

#### product description



### SCP992-1LD

Pluggable for SCALANCE XM408-4C, 1 x 1000 Mbit/s SC port, singlemode glass up to 10 km

- - spare part - - SCALANCE X accessory SCP992-1LD; pluggable for SCALANCE XM-400; 1x 1000 Mbps SC port, optical; single-mode optical up to max. 10 km.

### suitability for operation

SCALANCE XM408-4C

### interfaces

number of electrical/optical connections / for network components or terminal equipment / maximum	1
number of optical interfaces / for network components or terminal equipment / maximum	1
number of 1000 Mbit/s SC ports (LX)	1
design of the optical interface / for network components or terminal equipment	SC
wavelength / of the optical interface	1310 nm; Single-mode
connectable optical power relative to 1 mW	
• of the transmitter output / minimum	-9.5 dB
• of the transmitter output / maximum	-3 dB
• of the receiver input / maximum	-3 dB
optical sensitivity relating to 1 mW / of the receiver input / minimum	-19 dB
attenuation factor / of the FOC transmission link / minimum necessary	0 dB
range / at the optical interface / depending on the optical fiber used	0 ... 10 km
transmission method / for connection type 1	1000BASE-LX

### ambient conditions

ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• note	A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

### design, dimensions and weights

design	Plug-in transceiver
width	25.4 mm
height	10.2 mm
depth	56.5 mm
net weight	0.06 kg
fastening method	latched, only with SCALANCE XM408-4C

### standards, specifications, approvals

#### standard

• for emitted interference • for interference immunity	EN 61000-6-4 (Class A) EN 61000-6-2
certificate of suitability <ul style="list-style-type: none"><li>• CE marking</li><li>• C-Tick</li><li>• KC approval</li><li>• CCC / for hazardous zone according to GB standard</li><li>• CCC / for hazardous zone according to GB standard / as marking</li></ul>	EN 61000-6-2, EN 61000-6-4 Yes Yes No Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc
reference code <ul style="list-style-type: none"><li>• according to IEC 81346-2:2019</li></ul>	KEC
<b>further information / internet links</b>	
internet link <ul style="list-style-type: none"><li>• to website: Selection guide for cables and connectors</li><li>• to web page: selection aid TIA Selection Tool</li><li>• to website: Industrial communication</li><li>• to web page: SiePortal</li><li>• to website: Image database</li><li>• to website: CAx-Download-Manager</li><li>• to website: Industry Online Support</li></ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a> <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a> <a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a> <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a> <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a> <a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a> . (V4.7)

## Approvals / Certificates

### General Product Approval



[Declaration of Conformity](#)



### For use in hazardous locations



IECEx



ATEX

[CCC-Ex](#)

### Environment

[Confirmation](#)

last modified:

12/11/2024