



LV HRC fuse element, NH1, In: 250 A, gG, Un AC: 500 V, Un DC: 440 V, Combined indicator, Insulated grip lugs

| Model                                                                               |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
| product brand name                                                                  | SETRON                              |
| product designation                                                                 | LV HRC fuse link                    |
| design of the product                                                               | With blade contacts                 |
| design of an identification indicator                                               | Combination alarms                  |
| design of the switching contact                                                     | Non-corroding, silver-plated        |
| design of the fuse link                                                             | LV HRC fuse link                    |
| General technical data                                                              |                                     |
| size of fuse system according to EN 60269-1                                         | NH1                                 |
| mounting type                                                                       | insulated grip lugs                 |
| type of voltage of the operating voltage                                            | AC/DC                               |
| supply voltage                                                                      |                                     |
| • at AC                                                                             | 500 V                               |
| • at DC                                                                             | 440 V                               |
| Protection class                                                                    |                                     |
| protection class IP                                                                 | IP20, with connected conductors     |
| Breaking Capacity                                                                   |                                     |
| breaking capacity                                                                   |                                     |
| • at AC according to IEC 60269 rated value                                          | 120 kA                              |
| • at DC with time constant ≤ 10 ms according to IEC 60269 rated value               | 25 kA                               |
| Dissipation                                                                         |                                     |
| power loss [W]                                                                      | 18.2 W                              |
| power loss [W] for rated value of the current at AC in hot operating state per pole | 18.2 W                              |
| Mechanical Design                                                                   |                                     |
| width of the enclosure                                                              | 47.2 mm                             |
| mounting position                                                                   | Any, preferably vertical            |
| net weight                                                                          | 450 g                               |
| Environmental conditions                                                            |                                     |
| ambient temperature during operation                                                |                                     |
| • minimum                                                                           | -5 °C                               |
| • maximum                                                                           | 40 °C                               |
| environmental category                                                              | -20 to +50 at 95% relative humidity |
| environmental category during storage                                               | 90% at 20°C                         |
| Environmental footprint                                                             |                                     |
| global warming potential [CO2 eq] total                                             | 29.3 kg                             |
| global warming potential [CO2 eq] during manufacturing                              | 4.03 kg                             |
| global warming potential [CO2 eq] during operation                                  | 25.4 kg                             |
| global warming potential [CO2 eq] after end of life                                 | -0.232 kg                           |

|                                         |    |
|-----------------------------------------|----|
| Certificates                            |    |
| reference code according to IEC 81346-2 | FC |
| Approvals Certificates                  |    |
| General Product Approval                |    |



EG-Konf.

[Confirmation](#)



|                                                                                   |                               |                              |                               |                                                                                     |                                             |
|-----------------------------------------------------------------------------------|-------------------------------|------------------------------|-------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------|
| Marine / Shipping                                                                 | other                         | Environment                  |                               |                                                                                     |                                             |
|  | <a href="#">Miscellaneous</a> | <a href="#">Confirmation</a> | <a href="#">Miscellaneous</a> |  | <a href="#">Environmental Confirmations</a> |

|                                             |
|---------------------------------------------|
| Environment                                 |
| <a href="#">Environmental Confirmations</a> |

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NA6144>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NA6144>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NA6144](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NA6144)

##### CAX-Online-Generator


<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>



**-F**



# FU



---

last modified:

10/23/2024 

