



Figure similar

Article No. : 1FK7086-4CC74-1EA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed (100 K)	2,000 rpm
Number of poles	8
Rated torque (100 K)	18.0 Nm
Rated current	9.0 A
Static torque (60 K)	23.00 Nm
Static torque (100 K)	28.00 Nm
Stall current (60 K)	10.70 A
Stall current (100 K)	13.20 A
Moment of inertia	22.000 kgcm <sup>2</sup>
Efficiency	93.0 %

### Physical constants

Torque constant	2.12 Nm/A
Voltage constant at 20° C	138.0 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.31 Ω
Rotating field inductance	8.2 mH
Electrical time constant	26.50 ms
Mechanical time constant	0.45 ms
Thermal time constant	65 min
Shaft torsional stiffness	84,000 Nm/rad
Net weight of the motor	23.0 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	High Dynamic
Shaft height	80
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Feather key
Encoder system	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface

### Optimum operating point

Optimum speed	2,000 rpm
Optimum power	3.8 kW

### Limiting data

Max. permissible speed (mech.)	6,000 rpm
Max. permissible speed (inverter)	4,200 rpm
Maximum torque	105.0 Nm
Maximum current	71.0 A

### Recommended Motor Module

Rated inverter current	18 A
Maximum inverter current	54 A
Maximum torque	90.00 Nm