



cobre campo de acoplamento L tamanho da estrutura 2 (2000 A), montagem fixa



Versão	
nome da marca do produto	ALPHA 3200 Eco
Dados técnicos gerais	
quantidade de polos	3
componentes de uma ligação elétrica	Campo/Campo
Circuito principal	
corrente de serviço valor nominal	2 000 A
torque de aperto máximo	40 N·m
Projeto mecânico	
Peso líquido por ME	31,4 kg
Homologações certificados	
Environment	General Product Approval



[Environmental Con-
firmations](#)

[Confirmation](#)



[Miscellaneous](#)

General Product Ap- proval	Test Certificates	other
	Special Test Certific- ate	Confirmation

Outras informações

- Informações sobre a embalagem
[Informações sobre a embalagem](#)
- Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/pt/pt/Catalog/product?mlfb=8LK6037-0AA52>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/pt/ps/8LK6037-0AA52>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8LK6037-0AA52

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Curvas características

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

última alteração:

03/09/2025 

