

# Product data sheet

Specifications



## variable speed drive ATV312 - 1.1kW - 2.4kVA - 74W - 200..240 V- 1-phase supply

ATV312HU11M2

- ❗ Discontinued on: 17 February 2021
- ❗ To be end-of-service on: 01 January 2026

❗ Discontinued

### Main

|                                    |                                                                                                                                                                                                                 |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of Product                   | Altivar 312                                                                                                                                                                                                     |
| Product or Component Type          | Variable speed drive                                                                                                                                                                                            |
| Product destination                | Asynchronous motors                                                                                                                                                                                             |
| Product Specific Application       | Simple machine                                                                                                                                                                                                  |
| Assembly style                     | With heat sink                                                                                                                                                                                                  |
| Component name                     | ATV312                                                                                                                                                                                                          |
| Motor power kW                     | 1.1 kW                                                                                                                                                                                                          |
| Maximum Horse Power Rating         | 1.5 hp                                                                                                                                                                                                          |
| [Us] rated supply voltage          | 200...240 V - 15...10 %                                                                                                                                                                                         |
| Supply frequency                   | 50...60 Hz - 5...5 %                                                                                                                                                                                            |
| Phase                              | Single phase                                                                                                                                                                                                    |
| Line current                       | 12.1 A 200 V, I <sub>sc</sub> = 1 kA<br>10.2 A 240 V                                                                                                                                                            |
| EMC filter                         | Integrated                                                                                                                                                                                                      |
| Apparent power                     | 2.4 kVA                                                                                                                                                                                                         |
| Maximum transient current          | 10.4 A 60 s                                                                                                                                                                                                     |
| Power dissipation in W             | 74 W at nominal load                                                                                                                                                                                            |
| Speed range                        | 1...50                                                                                                                                                                                                          |
| Asynchronous motor control profile | Factory set : constant torque<br>Sensorless flux vector control with PWM type motor control signal                                                                                                              |
| Electrical connection              | AI1, AI2, AI3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1...LI6 terminal 0.00 in² (2.5 mm²) AWG 14<br>L1, L2, L3, U, V, W, PA, PB, PA/+, PC/- terminal 0.01 in² (5 mm²) AWG 10                                      |
| Supply                             | Internal supply for logic inputs 19...30 V 100 mA overload and short-circuit protection<br>Internal supply for reference potentiometer (2.2 to 10 kOhm) 10...10.8 V 10 mA overload and short-circuit protection |
| Communication port protocol        | CANopen<br>Modbus                                                                                                                                                                                               |
| IP degree of protection            | IP20 on upper part without cover plate<br>IP21 on connection terminals<br>IP31 on upper part<br>IP41 on upper part                                                                                              |
| Option card                        | Communication card CANopen daisy chain<br>Communication card DeviceNet<br>Communication card Fipio                                                                                                              |

Complementary

|                                     |                                                                                                                                                                                                                                                                                                                                                     |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply voltage limits               | 170...264 V                                                                                                                                                                                                                                                                                                                                         |
| Prospective line Isc                | 1 kA                                                                                                                                                                                                                                                                                                                                                |
| Continuous output current           | 6.9 A 4 kHz                                                                                                                                                                                                                                                                                                                                         |
| Output frequency                    | 0...500 Hz                                                                                                                                                                                                                                                                                                                                          |
| Nominal switching frequency         | 4 kHz                                                                                                                                                                                                                                                                                                                                               |
| Switching frequency                 | 2...16 kHz adjustable                                                                                                                                                                                                                                                                                                                               |
| Transient overtorque                | 170...200 % of nominal motor torque                                                                                                                                                                                                                                                                                                                 |
| Braking torque                      | 150 % 60 s with braking resistor<br>100 % with braking resistor continuously<br>150 % without braking resistor                                                                                                                                                                                                                                      |
| Regulation loop                     | Frequency PI regulator                                                                                                                                                                                                                                                                                                                              |
| Motor slip compensation             | Suppressable<br>Automatic whatever the load<br>Adjustable                                                                                                                                                                                                                                                                                           |
| Output voltage                      | <= power supply voltage                                                                                                                                                                                                                                                                                                                             |
| Tightening torque                   | AI1, AI2, AI3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1...LI6 5.31 lbf.in (0.6 N.m)<br>L1, L2, L3, U, V, W, PA, PB, PA/+, PC/- 10.62 lbf.in (1.2 N.m)                                                                                                                                                                                                 |
| Insulation                          | Electrical between power and control                                                                                                                                                                                                                                                                                                                |
| Analogue input number               | 3                                                                                                                                                                                                                                                                                                                                                   |
| Analogue input type                 | AI1 configurable voltage 0...10 V 30 V max 30000 Ohm<br>AI2 configurable voltage +/- 10 V 30 V max 30000 Ohm<br>AI3 configurable current 0...20 mA 250 Ohm                                                                                                                                                                                          |
| Sampling duration                   | AI1, AI2, AI3 8 ms analog<br>LI1...LI6 4 ms discrete                                                                                                                                                                                                                                                                                                |
| Response time                       | AOV, AOC 8 ms analog<br>R1A, R1B, R1C, R2A, R2B 8 ms discrete                                                                                                                                                                                                                                                                                       |
| Linearity error                     | +/- 0.2 % output                                                                                                                                                                                                                                                                                                                                    |
| Analogue output number              | 1                                                                                                                                                                                                                                                                                                                                                   |
| Analogue output type                | AOC configurable current 0...20 mA 800 Ohm 8 bits<br>AOV configurable voltage 0...10 V 470 Ohm 8 bits                                                                                                                                                                                                                                               |
| Discrete input logic                | Logic input not wired LI1...LI4), < 13 V<br>Negative logic (source) LI1...LI6), > 19 V<br>Positive logic (source) LI1...LI6), < 5 V, > 11 V                                                                                                                                                                                                         |
| Discrete output number              | 2                                                                                                                                                                                                                                                                                                                                                   |
| Discrete output type                | Configurable relay logic R1A, R1B, R1C) 1 NO + 1 NC - 100000 cycles<br>Configurable relay logic R2A, R2B) NC - 100000 cycles                                                                                                                                                                                                                        |
| Minimum switching current           | R1-R2 10 mA 5 V DC                                                                                                                                                                                                                                                                                                                                  |
| Maximum switching current           | R1-R2 2 A 250 V AC inductive, cos phi = 0.4 7 ms<br>R1-R2 2 A 30 V DC inductive, cos phi = 0.4 7 ms<br>R1-R2 5 A 250 V AC resistive, cos phi = 1 0 ms<br>R1-R2 5 A 30 V DC resistive, cos phi = 1 0 ms                                                                                                                                              |
| Discrete input number               | 6                                                                                                                                                                                                                                                                                                                                                   |
| Discrete input type                 | LI1...LI6) programmable 24 V, 0...100 mA PLC 3500 Ohm                                                                                                                                                                                                                                                                                               |
| Acceleration and deceleration ramps | S, U or customized<br>Linear adjustable separately from 0.1 to 999.9 s                                                                                                                                                                                                                                                                              |
| Braking to standstill               | By DC injection                                                                                                                                                                                                                                                                                                                                     |
| Protection type                     | Input phase breaks drive<br>Line supply overvoltage and undervoltage safety circuits drive<br>Line supply phase loss safety function, for three phases supply drive<br>Motor phase breaks drive<br>Overcurrent between output phases and earth (on power up only) drive<br>Overheating protection drive<br>Short-circuit between motor phases drive |

|                       |                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------|
|                       | Thermal protection motor                                                             |
| Insulation resistance | >= 500 mOhm 500 V DC for 1 minute                                                    |
| Local signalling      | for drive voltage 1 LED (red)<br>for CANopen bus status four 7-segment display units |
| Time constant         | 5 ms for reference change                                                            |
| Frequency resolution  | Analog input 0.1...100 Hz<br>Display unit 0.1 Hz                                     |
| Connector type        | 1 RJ45 Modbus/CANopen                                                                |
| Physical interface    | RS485 multidrop serial link                                                          |
| Transmission frame    | RTU                                                                                  |
| Transmission Rate     | 10, 20, 50, 125, 250, 500 kbps or 1 Mbps CANopen<br>4800, 9600 or 19200 bps Modbus   |
| Number of addresses   | 1...127 CANopen<br>1...247 Modbus                                                    |
| Number of drive       | 127 CANopen<br>31 Modbus                                                             |
| Marking               | CE                                                                                   |
| Operating position    | Vertical +/- 10 degree                                                               |
| Height                | 5.63 in (143 mm)                                                                     |
| Width                 | 4.21 in (107 mm)                                                                     |
| Depth                 | 5.98 in (152 mm)                                                                     |
| Net Weight            | 3.97 lb(US) (1.8 kg)                                                                 |

## Environment

|                                       |                                                                                                                                                                                                                                                                                           |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dielectric strength                   | 2040 V DC between earth and power terminals<br>2880 V AC between control and power terminals                                                                                                                                                                                              |
| Electromagnetic compatibility         | 1.2/50 µs - 8/20 µs surge immunity test level 3 IEC 61000-4-5<br>Electrical fast transient/burst immunity test level 4 IEC 61000-4-4<br>Electrostatic discharge immunity test level 3 IEC 61000-4-2<br>Radiated radio-frequency electromagnetic field immunity test level 3 IEC 61000-4-3 |
| Standards                             | IEC 61800-5-1<br>IEC 61800-3                                                                                                                                                                                                                                                              |
| Product Certifications                | CSA<br>NOM<br>C-tick<br>UL<br>DNV<br>GOST                                                                                                                                                                                                                                                 |
| Pollution degree                      | 2                                                                                                                                                                                                                                                                                         |
| Protective treatment                  | TC                                                                                                                                                                                                                                                                                        |
| Vibration resistance                  | 1 gn 13...150 Hz)EN/IEC 60068-2-6<br>1.5 mm 3...13 Hz)EN/IEC 60068-2-6                                                                                                                                                                                                                    |
| Shock resistance                      | 15 gn 11 ms EN/IEC 60068-2-27                                                                                                                                                                                                                                                             |
| Relative humidity                     | 5...95 % without condensation IEC 60068-2-3<br>5...95 % without dripping water IEC 60068-2-3                                                                                                                                                                                              |
| Ambient Air Temperature for Storage   | -13...158 °F (-25...70 °C)                                                                                                                                                                                                                                                                |
| Ambient air temperature for operation | 14...122 °F (-10...50 °C) without derating with protective cover on top of the drive)<br>14...140 °F (-10...60 °C) with derating factor without protective cover on top of the drive)                                                                                                     |
| Operating altitude                    | <= 3280.84 ft (1000 m) without derating<br>3280.84...6561.68 ft (1000...2000 m) with current derating 1 % per 100 m                                                                                                                                                                       |

## Ordering and shipping details

|                   |                                            |
|-------------------|--------------------------------------------|
| Category          | 22152-ATV320/ATV312/ATV32 (.25 THRU 7.5HP) |
| Discount Schedule | CP4B                                       |

|                   |               |
|-------------------|---------------|
| GTIN              | 3606480077531 |
| Returnability     | No            |
| Country of origin | ID            |

Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Number of Units in Package 1 | 1                        |
| Package 1 Height             | 7.87 in (20.0 cm)        |
| Package 1 Width              | 8.46 in (21.5 cm)        |
| Package 1 Length             | 9.06 in (23.0 cm)        |
| Package 1 Weight             | 4.33 lb(US) (1.966 kg)   |
| Unit Type of Package 2       | P06                      |
| Number of Units in Package 2 | 27                       |
| Package 2 Height             | 31.50 in (80.0 cm)       |
| Package 2 Width              | 31.50 in (80.0 cm)       |
| Package 2 Length             | 23.62 in (60.0 cm)       |
| Package 2 Weight             | 145.68 lb(US) (66.08 kg) |

Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                       |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                                                                                                                                                                                           |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                                                                                                                                                                                                                      |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                         |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                                                                                                                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                                                                |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)

ATV312HU11M2 is replaced by:

1x



variable speed drive, Altivar Machine ATV320, 1.1kW, 200 to 240V, 1 phase, compact  
ATV320U11M2C