



SENTRON, Switch disconnector 3LD, main switch, 3-pole, I_u: 16 A, Operating power / at AC-23 A at 400 V: 7.5 kW, installation in distribution boards, knob-operated mechanism, black, handle direct at the switch

| Model | |
|-------------------------------------------------------------------------------------|--------------------------------|
| product brand name | SENTRON |
| product designation | Switch disconnector |
| design of the product | Main switch |
| display version for switch position indicator manual operation | 1 ON - 0 OFF |
| type of switch | DIN-rail mounting |
| design of the actuating element | selector switch |
| color of the actuating element | black |
| design of handle | knob-operated mechanism, black |
| type of the driving mechanism motor drive | No |
| General technical data | |
| number of poles | 3 |
| size of switch disconnector | 1 |
| mechanical service life (operating cycles) typical | 100 000 |
| electrical endurance (operating cycles) | |
| • at AC-23 A at 690 V | 6 000 |
| operating frequency maximum | 50 1/h |
| degree of pollution | 3 |
| Voltage | |
| insulation voltage rated value | 690 V |
| surge voltage resistance rated value | 6 kV |
| operating voltage | |
| • at AC rated value | 690 V |
| operating frequency rated value | |
| • minimum | 50 Hz |
| • maximum | 60 Hz |
| Protection class | |
| protection class IP | IP40 |
| protection class IP on the front | IP40 |
| Dissipation | |
| power loss [W] for rated value of the current at AC in hot operating state per pole | 0.5 W |
| Main circuit | |
| operational current | |
| • at AC-21 at 690 V rated value | 16 A |
| • at AC-21 A at 240 V rated value | 16 A |
| • at AC-21 A at 400 V rated value | 16 A |
| • at AC-21 A at 440 V rated value | 16 A |
| • at AC-23 A at 400 V rated value | 16 A |

| | |
|----------------------------------------------------------------------------------|------------------|
| operating power | |
| • at AC-23 A at 240 V rated value | 4 kW |
| • at AC-23 A at 400 V rated value | 8 kW |
| • at AC-23 A at 440 V rated value | 7.5 kW |
| • at AC-23 A at 690 V rated value | 8 kW |
| • at AC-3 at 240 V rated value | 3 kW |
| • at AC-3 at 400 V rated value | 6 kW |
| • at AC-3 at 690 V rated value | 5.5 kW |
| Auxiliary circuit | |
| number of CO contacts for auxiliary contacts | 0 |
| number of NC contacts for auxiliary contacts | 0 |
| number of NO contacts for auxiliary contacts | 0 |
| operating voltage of auxiliary contacts at AC maximum | 500 V |
| continuous current of the auxiliary contact rated value | 10 A |
| insulation voltage of the auxiliary switch rated value | 500 V |
| Suitability | |
| suitability for use main switch | Yes |
| suitability for use switch disconnector | Yes |
| suitability for use EMERGENCY OFF switch | No |
| suitability for use safety switch | Yes |
| suitability for use maintenance/repair switch | Yes |
| Product details | |
| product feature can be locked into OFF position | Yes |
| accessories | |
| product extension optional | |
| • motor drive | No |
| • voltage trigger | No |
| number of connectable NC contacts for auxiliary contacts attachable maximum | 2 |
| number of connectable NO contacts for auxiliary contacts attachable maximum | 4 |
| number of connectable CO contacts for auxiliary contacts attachable maximum | 0 |
| number of bracket locks maximum | 2 |
| hasp thickness of the bracket locks | 4 ... 6 mm |
| Short circuit | |
| conditional short-circuit current with line-side fuse protection | |
| • at 690 V by gG fuse rated value | 50 kA |
| let-through current with closed switch | |
| • at 240 V for combination switch + gG fuse maximum | 3 kA |
| • at 440 V for combination switch + gG fuse maximum | 3 kA |
| • at 690 V for combination switch + gG fuse maximum permissible | 3 kA |
| I _{2t} value with closed switch | |
| • at 240 V for combination switch + gG fuse maximum | 2.5 kA2.s |
| • at 440 V for combination switch + gG fuse maximum | 2.5 kA2.s |
| • at 690 V for combination switch + gG fuse maximum | 3 kA2.s |
| design of the fuse link | |
| • for short-circuit protection of the main circuit required | fuse gL/gG: 20 A |
| • for short-circuit protection of the auxiliary switch required | fuse gL/gG: 10 A |
| operational current of upstream fuse rated value | 20 A |
| according UL | |
| operational current at AC according to UL 508/UL 60947-4-1 rated value | 16 A |
| operating voltage at AC at 50/60 Hz according to UL 508/UL 60947-4-1 rated value | 600 V |
| active power [hp] at AC at 480 V according to UL 508/UL 60947-4-1 rated value | 7.5 |
| active power [hp] at AC at 600 V according to UL 508/UL 60947-4-1 rated value | 10 |
| short-time withstand current (SCCR) at 600 V according to UL 508/UL 60947-4-1 | 5 kA |

| | |
|-----------------------------------------------------------------------|------------------------------------------------------------|
| continuous current of upstream fuse according to UL rated value | 50 A |
| type of fuse according to UL | RK5 |
| Connections | |
| AWG number as coded connectable conductor cross section solid maximum | |
| • | 10 |
| • | 18 |
| type of connectable conductor cross-sections for copper conductor | |
| • solid | 1x (1...6mm ²) |
| • finely stranded with core end processing | 1x (1...4mm ²) |
| • stranded | 1x (1..6mm ²) |
| type of connectable conductor cross-sections for auxiliary contacts | |
| • solid | 2x (0.75 ... 2.5 mm ²), 1x 4 mm ² |
| • finely stranded with core end processing | 2x (0.75 ... 1.5 mm ²), 1x 2.5 mm ² |
| • stranded | 2x (0.75 ... 2.5 mm ²), 1x 4 mm ² |
| type of electrical connection | |
| • for main current circuit | box terminal |
| • for auxiliary contacts | connection terminals |
| Mechanical Design | |
| height | 45 mm |
| width | 53 mm |
| depth | 91 mm |
| type of device | fixed mounting |
| fastening method | Built-in unit fixed-mounted version |
| fastening method | |
| • 4-hole front mounting | No |
| • front mounting with central attachment | No |
| • rail mounting | Yes |
| net weight | 168 g |
| Environmental conditions | |
| ambient temperature during operation | |
| • minimum | -25 °C |
| • maximum | 55 °C |
| ambient temperature during storage | |
| • minimum | -25 °C |
| • maximum | 55 °C |

Approvals Certificates

General Product Approval



[Confirmation](#)



| | | | |
|--------------------------|-------------------|-------|-------------|
| General Product Approval | Marine / Shipping | other | Environment |
|--------------------------|-------------------|-------|-------------|

[Miscellaneous](#)



[Miscellaneous](#)

[Confirmation](#)

[Environmental Confirmations](#)

Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD2030-0TK11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD2030-0TK11>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD2030-0TK11

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





