



**134F3027**

**FC-360Q11KT4E20H2BXCDXXSXXXXXAXBX**

Frequency converter  
 FC-360Q11KT4E20H2BXCDXXSXXXXXAXBX  
 VLT® AutomationDrive FC-(360) 360  
 11 KW / 15 HP, (T4) 380-480VAC (Three phased), IP20 / Chassis  
 RFI Class A2, (B) Brake Chopper  
 No Display (No Blind Cover)  
 (C) Coated PCB, Loadsharing  
 Standard Control Card, (BX) No B Option  
 Frame: J4  
 Other options according to Model code

**Model code:** FC-360Q11KT4E20H2BXCDXXSXXXXXAXBX

Danfoss VLT® AutomationDrive FC 360 is dedicated to industry applications, like pumps & fans, conveyors, extruders, draw benches and etc, covering power range from 0.37 to 75kW, 380-480V three phase. With a wide range of powerful standard and optional features, user-friendly design of HMI and application selections, high reliability against harsh environment, the VLT® AutomationDrive FC 360 provides high performance and versatile functions at the lowest overall cost of ownership, making it perfect match for OEM customers.  
 Note: Built-in DC choke for whole power range. Built-in braking chopper up to 22kW. LCP Displays are external options.

**PRODUCT DETAILS**

<b>Gross weight</b>		8.6 kg
<b>Net weight</b>		7.85 kg
<b>Volume</b>		0 l
<b>EAN</b>		5710107427826
<b>Sales restriction control</b>		
<b>Matr grp for sales restriction</b>	0001	No grouping
<b>VLT® AUTOMATIONDRIVE FC 360 SERIES</b>		
<b>Product View (Switch)</b>	GLBL	Global (Standard)
<b>Product Group</b>	FC-	VLT® AutomationDrive FC-
<b>Series</b>	360	(360) 360
<b>Power</b>	Q	Normal Overload
<b>Power Size</b>	11K	11 KW / 15 HP
<b>Voltage</b>	T4	(T4) 380-480VAC (Three phased)
<b>Enclosure</b>	E20	IP20 / Chassis
<b>RFI Filter</b>	H2	RFI Class A2
<b>Brake &amp; Stop</b>	B	(B) Brake Chopper
<b>Display</b>	X	No Display (No Blind Cover)
<b>Coating</b>	C	(C) Coated PCB
<b>Mains Option</b>	D	Loadsharing
<b>Adaptation A</b>	X	Standard Cable Entries
<b>Adaptation B</b>	X	No Adaptation
<b>Special Version</b>	SXXX	Latest release – Std. Software
<b>Software Language Pack</b>	X	Standard Language Pack
<b>Control Card</b>	AX	Standard Control Card

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | FC-360Q11KT4E20H2BXCXXSXXXXXAXBX

## PRODUCT DETAILS

<b>B Option</b>	BX	(BX) No B Option
<b>Frame Size</b>	J4	J4
<b>Typecode Part 1</b>		FC-360Q11KT4E20H2BXC
<b>Typecode Part 2</b>		DXXSXXXXXAXBX
<b>Product Catalog</b>	NO_VIEW	NO VIEW
<b>Calculated Gross Weight [kg]</b>		10.15
<b>Calculated Net Weight [kg]</b>		9.4
<b>Material Gross Weight</b>		8.6
<b>Material Net Weight</b>		7.85
<b>Vendor</b>	ERR01	Cannot Determine Vendor
<b>Recommended Factory</b>	ERR01	Cannot Determine Vendor
<b>Modelcode01</b>		FC-360Q11KT4E20H2BXC
<b>Modelcode02</b>		DXXSXXXXXAXBX

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

## Accessories

**132B0268** [🔗](#)

Terminal Cover for MCB, J5, FC 360

**132B0267** [🔗](#)

Terminal Cover for MCB, J4, FC 360

**132B0266** [🔗](#)

Terminal Cover for MCB, J3, FC 360

**132B0265** [🔗](#)

Terminal Cover for MCB, J2, FC 360

**132B0263** [🔗](#)

Terminal Cover for MCB, J1, FC 360

**132B0262** [🔗](#)

LCP Blind cover, IP20/21

Use the blind cover to mount on a VLT® Midi Drive FC 280 when you does not need a control panel.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**


---



**132B0260** [🔗](#)  
**Decoupling Plate mounting kit, J4, J5**  
 Decoupling Plate mounting kit, J4, J5



**132B0256** [🔗](#)  
**Control Cassette (with Profibus)**



**132B0254** [🔗](#)  
**VLT® Control Panel LCP 21, numeric**  
 VLT® Control Panel LCP 21 Numerical



**132B0102** [🔗](#)  
**LCP Remote Mounting Kit, w/ 3m cable**  
 Remote installation kit for VLT Micro Drive FC 51 for installing an LCP 11 or LCP 12 control unit in a control cabinet door or similar. (can also be retrofitted).  
 Contains fastening elements, seal and 3 m connection cable with plugs.  
 LCP is not included in the scope of delivery.  
 Minimum delivery quantity: 6 (in a collective box with individual packaging)



**132B0132** [🔗](#)  
**LCP Remote Mounting Cable, 3m**



**132B0285** [🔗](#)  
**Decoupling Plate mounting kit, J7**  
 Decoupling Plate mounting kit, J7



**132B0284** [🔗](#)  
**Decoupling Plate mounting kit, J6**  
 Decoupling Plate mounting kit, J6



**132B0283** [🔗](#)  
**VLT® Resolver Input MCB 103, FC 360**  
 VLT® Resolver Input MCB 103, FC 360



**132B0282** [🔗](#)  
**VLT® Encoder Input MCB 102, FC 360**



**132B0281** [🔗](#)  
**Adaptor, Graphical LCP**  
 Graphic LCP adapter for LCP102

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



**132B0801** [🔗](#)

**VLT® Control Panel LCP 23**

Graphical control panel for FC360, equipped with Chinese, English and Portuguese language



**132B1461** [🔗](#)

**Decoupling mounting kit, FC360 J7 90kW**

Decoupling mounting kit,FC360 J7 90kW

Spare Parts



**132B0279** [🔗](#)

**Fan 92x38 Ip21 for frame size J4**

Fan 92x38 Ip21 for frame size J4



**132B0264** [🔗](#)

**Relay&RS485 Header for frame size J1-J5**



**132B0257** [🔗](#)

**Control Cassette (with ProfiNet)**

Control Cassette (with ProfiNet)



**132B0256** [🔗](#)

**Control Cassette (with Profibus)**



**132B0255** [🔗](#)

**Standard Control Cassette**



**132B0284** [🔗](#)

**Decoupling Plate mounting kit, J6**

Decoupling Plate mounting kit, J6

Image coming soon

**134B6778** [🔗](#)

**VLT® Profibus DP V1 FC-360, coated**

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Spare Parts**

---

Image  
coming  
soon**134B6779** **VLT® PROFINET FC-360, coated**

---

**Services**

---

**130R1002** **DrivePro ExWarr Onsite PG01 36 months**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

**130R1010** **DrivePro ExWarr Onsite PG02 24 months**

DrivePro® On-site Extended Warranty provides repair at the customer site, or replacement at the customer site.

You can only order DrivePro® Extended Warranty when purchased with a new drive. For drives previously shipped or purchased; contact your local Danfoss Drives sales office for extended warranty contract options.

---

**For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Services**

---

**134F2981** [🔗](#)**FC-360H15KT4E20H2BXCDXXSXXXXAXBX**

Frequency converter

FC-360H15KT4E20H2BXCDXXSXXXXAXBX

VLT® AutomationDrive FC-(360) 360

15 KW / 20 HP, (T4) 380-480VAC (Three phased), IP20 / Chassis

RFI Class A2, (B) Brake Chopper

No Display (No Blind Cover)

(C) Coated PCB, Loadsharing

Standard Control Card, (BX) No B Option

Frame: J4

Other options according to Model code

**Model code:** FC-360H15KT4E20H2BXCDXXSXXXXAXBX

Danfoss VLT® AutomationDrive FC 360 is dedicated to industry applications, like pumps & fans, conveyors, extruders, draw benches and etc, covering power range from 0.37 to 75kW, 380-480V three phase.

With a wide range of powerful standard and optional features, user-friendly design of HMI and application selections, high reliability

against harsh environment, the VLT® AutomationDrive FC 360 provides high performance and versatile functions at the lowest overall

cost of ownership, making it perfect match for OEM customers.

Note: Built-in DC choke for whole power range. Built-in braking chopper up to 22kW. LCP Displays are external options.

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.