

HMI connecting cable 5 m for door mounting



|                                               |                      |
|-----------------------------------------------|----------------------|
| product brand name                            | SIRIUS               |
| product category                              | Connecting cables    |
| product designation                           | HMI connecting cable |
| design of the product                         | 5 m, round           |
| manufacturer's article number of soft starter |                      |
| •                                             | 3RW50                |
| •                                             | 3RW51                |
| •                                             | 3RW52                |
| •                                             | 3RW55                |

|                                                         |                                                  |
|---------------------------------------------------------|--------------------------------------------------|
| General technical data                                  |                                                  |
| Substance Prohibittance (Date)                          | 02/15/2018                                       |
| Weight                                                  | 0.286 kg                                         |
| Ambient conditions                                      |                                                  |
| ambient temperature during storage and transport        | -40 ... +80 °C                                   |
| Electrical Safety                                       |                                                  |
| protection class IP on the front according to IEC 60529 | IP20                                             |
| touch protection on the front according to IEC 60529    | finger-safe, for vertical contact from the front |
| Approvals Certificates                                  |                                                  |
| General Product Approval                                | EMV                                              |



[Confirmation](#)



[KC](#)

|                                |                                                                                     |                                                                                       |
|--------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| For use in hazardous locations | Test Certificates                                                                   | Marine / Shipping                                                                     |
| <a href="#">Miscellaneous</a>  | <a href="#">Type Test Certificates/Test Report</a>                                  |                                                                                       |
|                                |  |    |
|                                |                                                                                     |  |
|                                |                                                                                     |  |
| Marine / Shipping              | other                                                                               | Environment                                                                           |



[Confirmation](#)

[Environmental Confirmations](#)

#### Further information

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5980-0HC60>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5980-0HC60>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5980-0HC60>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5980-0HC60&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5980-0HC60&lang=en)

**Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5980-0HC60/char>

**Characteristic: Installation altitude**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5980-0HC60&objecttype=14&gridview=view1>

**Simulation Tool for Soft Starters (STS)**

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

---

last modified:

12/15/2020 

