



Figure similar

connection cable PN for KTPX00(F) Mobile (PROFINET) length: 8 m, scope of supply: 1 connection cable

General information			
Product type designation	Connecting cable		
Standards, approvals, certificates			
CE mark	Yes		
cULus	Yes		
RCM (formerly C-TICK)	Yes		
KC approval	Yes		
Suitable for safety functions	Yes		
Ambient conditions			
Ambient temperature during operation			
• min.	0 °C		
• max.	55 °C		
Ambient temperature during storage/transportation			
• min.	-20 °C		
• max.	60 °C		
Cables			
Cable length	8 m		
Maximum tensile load	300 N		
Color of cable sheath			
• green	Yes		
Scope of supply			
Delivery quantity in pieces	1		
Other			
Merchandise	Yes		
Manufacturer name	On request		
Note:	halogen-free according to EN 50267-2-1		
Classifications			
		Version	Classification
	eClass	14	27-33-02-92
	eClass	12	27-33-02-92
	eClass	9.1	27-33-02-92
	eClass	9	27-33-02-92
	eClass	8	27-24-92-03
	eClass	7.1	27-24-92-03
	eClass	6	27-24-92-03
	ETIM	10	EC002584
	ETIM	9	EC002584

ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

[Miscellaneous](#)



Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415

<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified:

9/10/2025