



SIMATIC S7-1500, TM FAST Field Adaptable High-Speed Technology, programmable with Intel(R) Quartus(R) Prime software, 8xDI, 8xDQ, 4xDIQ 24 V, 8xRS485 DIQ, for extremely short response time of less than 1 µs

General information	
Product type designation	TM FAST
Firmware version	V1.0
FW update possible	Yes
Product function	
I&M data	Yes; I&M0 to I&M3
Isochronous mode	Yes
Engineering with	
STEP 7 TIA Portal configurable/integrated from version	STEP 7 V17 with HSP or higher
PROFINET from GSD version/GSD revision	GSDML V2.35
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Load voltage L+	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	100 mA; without load
Power	
Power consumption from the backplane bus	1.3 W
Power loss	
Power loss, typ.	4 W
Address area	
Address space per module	
Inputs	32 byte
Outputs	32 byte
Digital inputs	
Number of digital inputs	12; including 4 DIQs
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Input voltage	
Type of input voltage	DC
Rated value (DC)	24 V
for signal "0"	-5 ... +5 V
for signal "1"	+11 to +30V
permissible voltage at input, min.	-5 V; -5 V continuous, -30 V brief reverse polarity protection
permissible voltage at input, max.	30 V

Input current	
• for signal "1", typ.	2.5 mA
Input frequency	
• For signal interface 24 V asymmetrical	200 kHz
• For signal interface RS 422 symmetrical	5 MHz
• For signal interface TTL (5 V) asymmetrical	1 MHz
Input delay (for rated value of input voltage)	
• Minimum pulse width for program reactions	application specific below 1 µs possible
for standard inputs	
— parameterizable	Yes; customer defined / 0.001 / 0.003 / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
Cable length	
• shielded, max.	100 m
Digital outputs	
Number of digital outputs	12; including 4 DIQs
Current-sinking	Yes; 8 push-pull outputs
Current-sourcing	Yes
Short-circuit protection	Yes; electronic/thermal
• Response threshold, typ.	0.2 A; for DQ; 0.9 A for DIQ
Switching capacity of the outputs	
• with resistive load, max.	0.1 A; 0.3 A for DIQs
Load resistance range	
• lower limit	240 Ω; 80 ohms for DIQs
• upper limit	12 kΩ
Output voltage	
• Type of output voltage	DC
• for signal "1", min.	23.2 V; L+ (-0.8 V), L+ (-1.3 V) for DIQs
Output current	
• for signal "1" rated value	0.1 A; 0.3 A for DIQs
• for signal "1" permissible range, max.	0.12 A; 0.36 A for DIQs
• for signal "1" minimum load current	2 mA
• for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
• "0" to "1", typ.	420 ns; for DQn
• "1" to "0", typ.	420 ns; for DQn
Switching frequency	
• with resistive load, max.	200 kHz; 1 kHz for DIQs
• For signal interface 24 V asymmetrical	200 kHz; 1 kHz for DIQs
• For signal interface RS 422 symmetrical	2 MHz
• For signal interface TTL (5 V) asymmetrical	200 kHz
Cable length	
• shielded, max.	30 m
Encoder	
Interface types	
• TTL 5 V	Yes; 8 channels (direction switchable)
• RS 422	Yes; 8 channels (direction switchable)
• Source/sink input	Yes
• Input characteristic curve in accordance with IEC 61131, type 3	Yes
Isochronous mode	
Bus cycle time (TDP), min.	250 µs
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	Yes; for RS485/RS422/TTL Input

• Short-circuit • Group error	Yes; Thermal overload protection Yes																																				
Diagnostics indication LED																																					
• RUN LED • ERROR LED • MAINT LED • Monitoring of the supply voltage (PWR-LED) • Channel status display • for channel diagnostics	Yes; green LED Yes; red LED Yes; Yellow LED Yes; green LED Yes; green LED Yes; red LED																																				
Potential separation																																					
Potential separation channels																																					
• between the channels • between the channels and backplane bus • Between the channels and load voltage L+	No Yes No																																				
Isolation																																					
Isolation tested with	707 V DC (type test)																																				
Ambient conditions																																					
Ambient temperature during operation																																					
• horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max.	-30 °C 60 °C -30 °C 40 °C																																				
Altitude during operation relating to sea level																																					
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200MP system manual																																				
Decentralized operation																																					
to SIMATIC S7-300	Yes																																				
to SIMATIC S7-400	Yes																																				
to SIMATIC S7-1200	Yes																																				
to SIMATIC S7-1500	Yes																																				
to standard PROFINET controller	Yes																																				
Dimensions																																					
Width	35 mm																																				
Height	147 mm																																				
Depth	129 mm																																				
Weights																																					
Weight, approx.	300 g																																				
Classifications																																					
	<table><tr><td></td><td>Version</td><td>Classification</td></tr><tr><td>eClass</td><td>14</td><td>27-24-22-05</td></tr><tr><td>eClass</td><td>12</td><td>27-24-22-05</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-22-05</td></tr><tr><td>eClass</td><td>9</td><td>27-24-22-05</td></tr><tr><td>eClass</td><td>8</td><td>27-24-22-05</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-22-05</td></tr><tr><td>eClass</td><td>6</td><td>27-24-22-05</td></tr><tr><td>ETIM</td><td>10</td><td>EC001422</td></tr><tr><td>ETIM</td><td>9</td><td>EC001422</td></tr><tr><td>ETIM</td><td>8</td><td>EC001422</td></tr><tr><td>ETIM</td><td>7</td><td>EC001422</td></tr></table>		Version	Classification	eClass	14	27-24-22-05	eClass	12	27-24-22-05	eClass	9.1	27-24-22-05	eClass	9	27-24-22-05	eClass	8	27-24-22-05	eClass	7.1	27-24-22-05	eClass	6	27-24-22-05	ETIM	10	EC001422	ETIM	9	EC001422	ETIM	8	EC001422	ETIM	7	EC001422
	Version	Classification																																			
eClass	14	27-24-22-05																																			
eClass	12	27-24-22-05																																			
eClass	9.1	27-24-22-05																																			
eClass	9	27-24-22-05																																			
eClass	8	27-24-22-05																																			
eClass	7.1	27-24-22-05																																			
eClass	6	27-24-22-05																																			
ETIM	10	EC001422																																			
ETIM	9	EC001422																																			
ETIM	8	EC001422																																			
ETIM	7	EC001422																																			
Approvals / Certificates																																					
General Product Approval																																					



[Miscellaneous](#)

[China RoHS](#)



General Product Approval	For use in hazardous locations
--------------------------	--------------------------------

[KC](#)



[FM](#)

[CCC-Ex](#)



IECEX



For use in hazardous locations

[Type Examination Certificate](#)

[Miscellaneous](#)

last modified:

10/23/2025