

**134G7282****CONVERSOR FREQUENCIA FC102N315T4E54H2XGC**

Conversores de Frequências

FC-102N315T4E54H2XGC3XXSXXXAXBXXXXX

VLT® HVAC Drive FC-102

(N315) 315 KW / 450 HP, Trifásico

380 - 480 VCA, (E54) IP54 / Type 12

Filtro de RFI

Sem circuito de frenagem

Painel de contr local gráfico

Placas eletrôn. envernizadas, Desconexão RedeElétr + Fusível

Última versão do SW padrão

Sem Opcional A, Sem Opcionais B

Sem opcional C1, Sem opcional D

quadro: D7H

Outras opções de acordo com o código do modelo

Código Danfoss: FC-102N315T4E54H2XGC3XXSXXXAXBXXXXX

O VLT® HVAC Drive é dedicado a aplicações de ventilação, aquecimento e refrigeração. Com uma vasta linha de potentes características padrão e opcionais, esse conversor proporciona o menor custo geral de propriedade.

View Efficiency Data**PRODUCT DETAILS**

Peso bruto		256 kg
Peso líquido		206 kg
Volume		0 l
EAN		5710107621545
Sales restriction control		
Matr grp for sales restriction	0001	No grouping
VLT® HVAC DRIVE FC 100 SERIES		
Visão do produto (Alterar)	GLBL	Global (Padrão)
Grupo de produtos	FC-	VLT® HVAC Drive FC-
Série	102	102
Potência Nominal	N315	(N315) 315 KW / 450 HP
Fase	T	Trifásico
Tensão de rede	4	380 - 480 VCA
Enclosure	E54	(E54) IP54 / Type 12
Filtro de RFI	H2	Filtro de RFI
Freio - Safe Stop	X	Sem circuito de frenagem
LCP	G	Painel de contr local gráfico
Revestimento de PCB	C	Placas eletrôn. envernizadas
Opcional de rede elétrica	3	Desconexão RedeElétr + Fusível
Adaptação A	X	Entradas de cabo padrão
Adaptação B	X	Sem adaptação
Versão do software	SXXX	Última versão do SW padrão
Pacote de idioma padrão	X	Pacote de Idioma Padrão
Opcional A	AX	Sem Opcional A
Opcional B	BX	Sem Opcionais B

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

C0 Option MCO	CX	No C0 option
Opcional C1	X	Sem opcional C1
Software do opcional C	XX	Sem opção de software
Opcional D	DX	Sem opcional D
Frame Size	D7H	D7H
Catálogo de produtos	NO_VIEW	SEM EXIBIÇÃO
Codificação Parte 1		FC-102N315T4E54H2XGC
Codificação Parte 2		3XXSXXXXXAXBXCXXXXDX
Potência 110% (NO) [KW]		315
Altura [mm]		1978,0
Largura s/ opcionais C [mm]		420,0
Profundidade [mm]		386,0
Profund. c/ opcional A/B [mm]		386,0
kVA		407
Perdas NO [W]		6663
Perdas NO [W]		5703
Corrente constante (NO) [A]		588
Corrente intermitente (NO) [A]		647
Corrente constante (NO) [A]		535
Corrente intermitente (NO) [A]		588
Peso Bruto Calculado [kg]		200.3
Peso líquido calculado [kg]		200
Material Gross Weight		256
Material Net Weight		206
Fornecedor	ERR01	Não é possível determ fornec
Fábrica recomendada	ERR01	Não é possível determ fornec
Código do modelo 01		FC-102N315T4E54H2XGC
Modelocode02		3XXSXXXXXAXBXCXXXXDX

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Acessórios

**130B1235** [🔗](#)**MOD. COMUM. MCA120 PROFINET SRT coated**

MCA 120 PROFINET interface

With reinforced coating (class 3C3 / IEC 60721-3-3)

-Supports operation on PROFINET network with extensive characteristics

-DCP support for easy setting u. Communication parameters via the PLC

-on Board web-Page with Drive Status

-parameterization with the MCT10 software

- 2-port version, reduced external hardware

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Acessórios

**130B1243** **PLACA ELETRÔNICA P/ CONVERSOR FREQUÊNCIA**

I / O extension for FC 100, easy to retrofit thanks to modular technology.

Analog inputs / outputs galvanically isolated.

Expands the analog inputs / outputs by:

3 analog inputs: 0 ... 10V / Pt1000 / Ni1000

3 analog outputs: 0 ... 10V

Time switch (RTC backup): lithium cell for 10 years

**130B1219** **VLT® EtherNet IP MCA 121, coated**

A EtherNet/IP amplia a EtherNet comercial pronta para o Protocolo Industrial Comum (CIP™) – o mesmo protocolo de camadas superiores e modelo de objeto encontrado no DeviceNet. Interruptor integrado de alto desempenho que permite topologia de linha e elimina a necessidade de interruptores externos. Topologia Device Level Ring (DLR) para maior disponibilidade do sistema. Baseada em CIP™, possibilita a reutilização do programa PLC ao migrar do DeviceNet para o EtherNet/IP. Servidor web integrado fornece diagnóstico remoto e leitura dos parâmetros básicos do drive. A notificação por e-mail oferece acesso rápido a informações de advertências ou alarmes. Comunicação unicast e multicast para melhor utilização da rede. Certificado por ODVA para o cumprimento dos mais novos padrões.

**130B1212** **KIT MCB101 I/O REVESTIDO**

MCB 101 - Advanced I / O option

Expands the number of freely programmable

Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.

- 2 analog inputs 0 - 10 V.

- 2 digital outputs NPN / PNP switchable 24 V

- 1 analog output 0/4 - 20 mA

with reinforced coating

**130B1210** **CARTÃO DE RELÊS EXTRAS MCB105 COM VERNIZ**

Relay extension for FC 100 and FC 300.

Extension with 3 additional load relays (changeover contacts),
easy to retrofit thanks to modular technology.

Painted version for harsh environments,
easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A

**130B1208** **CARTÃO 24V MCB 107, COATED**

Conecte a alimentação CC externa para manter a seção de controle e qualquer opcional instalado ligados durante faltas de energia. Permite a operação completa do LCP (incluindo a programação do parâmetro) e todos os opcionais instalados sem ligação à rede elétrica.

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Acessórios

**130B1202** **MCA104-OPCIONAL DEVICENET FC300 COATED**

MCA 104 - DeviceNet interface Option for FC300 and FC100 for mounting on the control card. Painted version

**130B1200** **VLT® PROFIBUS DP V1 MCA 101 ENVERNIZADO**

Fornecer ampla compatibilidade, alto nível de disponibilidade, suporte a todos os principais fornecedores de PLC e compatibilidade com versões futuras. Comunicação rápida e eficiente, instalação transparente, diagnóstico e parametrização avançados e autoconfiguração eficiente de dados de processo com a utilização do arquivo GSD. Parametrização acíclica usando o PROFIBUS DP-V1, PROFIdrive ou as máquinas de estado de perfil do FC da Danfoss, PROFIBUS DP-V1, Classe Mestre 1 e 2.

**130B1296** **VLT® MODBUS TCP MCA 122 ENVERNIZADO**

O primeiro protocolo industrial para automação baseado em Ethernet Conecta-se com redes baseadas em Modbus TCP. Capaz de lidar com intervalos de conexão de 5 ms ou mais em ambas as direções, o que o coloca entre os dispositivos Modbus TCP com o mais rápido desempenho no mercado. Para redundância mestre, ele apresenta troca quente entre dois mestres.

**130B1001** **SOFTWARE DE PROGRAMAÇÃO MCT10/5 USUÁRIOS**

Uma ferramenta interativa para configuração on-line/off-line rápida e fácil de um drive VLT® ou soft starter usando um PC. Configure redes de comunicação e faça backup de programações de parâmetros relevantes. Controle e configure sistemas simultaneamente e monitore todo o sistema com mais eficácia para um monitoramento, diagnóstico, resolução de problemas (alarmes/advertências) mais rápidos e melhor manutenção preventiva.

**130B1000** **MCT 10 - USER**

Uma ferramenta interativa para configuração on-line/off-line rápida e fácil de um drive VLT® ou soft starter usando um PC. Configure redes de comunicação e faça backup de programações de parâmetros relevantes. Controle e configure sistemas simultaneamente e monitore todo o sistema com mais eficácia para um monitoramento, diagnóstico, resolução de problemas (alarmes/advertências) mais rápidos e melhor manutenção preventiva.

**130B1135** **VLT PROFINET MCA 120, uncoated**

MCA 120 PROFINET interface

- Supports operation on PROFINET network with extensive properties
- DCP support for easy setting u. Communication parameters via the PLC
- On Board web-Page with Drive Status
- Parameterization with the MCT10 software
- 2 port version, reduced external hardware

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Acessórios

**130B1125** **OPCIONAL DE I/O ADICIONAIS - FC300**

MCB 101 - Advanced I / O option

Expands the number of freely programmable Control inputs and outputs around the following I / Os:

- 3 digital inputs opto-decoupled 0 - 24 V.
- 2 analog inputs 0 - 10 V.
- 2 digital outputs NPN / PNP switchable 24 V
- 1 analog output 0/4 - 20 mA

**130B1124** **LCP NUMERICO - FC 302**

Numerical control unit for FC 100 and FC 300. Allows access to all device parameters.

Quick menu for brief commissioning. Manual / auto switchover and alarm acknowledgment.

**130B1117** **KIT REMOTO FC300**

O kit inclui fixadores, cabo de 3 m e vedação - O LCP não está incluído.

**130B1110** **MCB 105 RELAY OPTION**

Relay extension for FC 100 and FC 300. Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A

Max. Load 240V AC (Cos Phi 0.4): 0.2 A

Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A

**130B1143** **MCB109 CARTÃO DE I/O HVAC**

I / O expansion for FC 100, through modular technology easy to retrofit. Analog inputs/outputs galvanically isolated.

Expands the analog inputs / outputs by:

3 analog inputs: 0 ... 10V / Pt1000 / Ni1000

3 analog outputs: 0 ... 10V

Time switch (RTC backup): lithium cell for 10 years

**130B1137** **MCB 112 ATEX Thermistor Cartão Revestido**

MCB 112 PTC - thermistor relay MS220DA In connection with ATEX certified explosion-proof motors for full motor protection. Certified PTC sensors are the sole protection required.

Integrable module with ATEX-compliant full thermal motor protection

1 PTB-certified PTC thermistor input

1 switch-off signal for using the Safe Stop function

1 logic output for error identification

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Acessórios

**130B1100** **PLACA DE PROFIBUS FC 302**

Fornecer ampla compatibilidade, alto nível de disponibilidade, suporte a todos os principais fornecedores de PLC e compatibilidade com versões futuras. Comunicação rápida e eficiente, instalação transparente, diagnóstico e parametrização avançados e autoconfiguração eficiente de dados de processo com a utilização do arquivo GSD. Parametrização acíclica usando o PROFIBUS DP-V1, PROFIdrive ou as máquinas de estado de perfil do FC da Danfoss, PROFIBUS DP-V1, Classe Mestre 1 e 2.

**175Z0929** **CABO PARA LCP , 3 M**

Cable for control panel (LCP), 3 meters

Works with the following LCP:

Alphanumeric control panel LCP3 - 175N0131

VLT® LCP 102 Graphic Display - 130B1107

VLT® LCP 101 Numeric Display - 130B1124

VLT® LCP 102 Graphic display IP66 - 130B1078

Product group: F1

Image
coming
soon

175U0009 **SUPORTES FIXACAO P/ CONVERSOR FREQUENCIA**

Mounting angle for flatpack resistor 200W

**175N2584** **MCA 121 EtherNet/IP coated gateway****134B5925** **Transmissor de Pressão PTU 025 200-690V**

VLT PTU 025 pressure transmitter unit
for external attachment to frequency converters

VLT HVAC Drive FC-102 IP55 / IP66 on one
the cable entries suitable for M25

- with four pressure sensors 2x 0-500 Pa;

1x 0-1000 Pa; 1x 0-2500 Pa

- eight hose connections D 5mm

- Can be positioned 360 ° around the longitudinal axis

Software version of the frequency converter FC-102

at least 5.20 am required

Mounting thread: M25

Dimensions LxW: 155mm x 38mm

(Length with hose support rail 260.5mm)

Degree of protection: IP66

Image
coming
soon

134B5224 **REMOTO LCP CABO 5M**

Remote mounting kit for LCP with cover for outdoor mounting with 5 m (16
ft) cable

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Acessórios

**134B5223** **KIT DE MONTAGEM LCP102 W. CABO 3M**

Remote mounting kit for LCP with cover for outdoor mounting with 3 m (10 ft) cable

**134B0460** **PAINEL CONTROLE P/ CONVERSOR FREQUENCIA**

With VLT® Wireless Communication Panel LCP 103 you can communicate with MyDrive® Connect - an app that can be downloaded for iOS and Android based smartphones. MyDrive® Connect makes commissioning easy, monitor and maintain tasks on your frequency converter. VLT® Wireless Communication Panel LCP 103 shows the current status of the drive (On, Warning, Alarm, Wifi connection) via built-in LED. Detailed information is also available using MyDrive® Connect. Here do you have access to i.a. status, menu and alerts. You can also see graphs over the latest available data.

The new VLT® Wireless Communication Panel LCP 103 allows you to wireless communication to the following drives:

- VLT® HVAC Drive FC 102
- VLT® Refrigeration Drive FC 103
- VLT® AQUA Drive FC 202
- VLT® AutomationDrive FC 302

[!] Note!

LCP 103 only works on frequency converters produced in 2018 (White USB stik).

Product group: R1

Image
coming
soon

130B6447 **MCB 141 OPCIONAL DE SEGURANCA EXTERNO**

Amplia o recurso Safe Torque Off dos drives VLT® com funções de segurança adicionais: Parada segura 1 (SS1), velocidade limitada com segurança (SLS), velocidade máxima segura (SMS) e monitor de velocidade segura (SSM).

**130B1144** **MODULO MCA109 BACNET**

Open communication protocol dedicated to building automation

- Efficient integration of all parts of building automation equipment
- BACnet: standard for building automation worldwide
- International standard ISO 16484-5
- can be used in all sizes of building automation systems
- the Drive communicates easily with construction management systems running the BACnet protocol
- can be easily integrated into the network of existing control equipment

Product group: R1

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Acessórios

**130B1244** **MODULO MCA190 BACNET, envernizada**

A. Device profile: Application-Specific-Controller (B-ASC)

Supported objects: Analog Input, Analog Output, Analog Value, Binary Input, binary output,

Binary Value, Device, Multi-State Output, Notification Class

Protocol: Building automation world standard ISO 16484-5

Data Link Layer: MS / TP 9600, 19200, 38400, 76800

Data sharing: ReadProperty-B, DS-RP-B

ReadPropertyMultiple-B, DS-RPM-B

WriteProperty-B, DS-WP-B

WritePropertyMultiple-B, DS-WPM-B

Alarm and Notification Internal-B, AE-N-I-B

Event Notification: ACK-B, AE-ACK-B

Information-B, AE-INFO-B

Device and Network Dynamic Device Binding-A, DM-DDB-A

Management: Dynamic Device Binding-B, DM-DDB-B

**130B0295** **EMBALAGEM COM ACESSORIOS CONTENDO PLUGS****134B1586** **VLT® BACNET/IP MCA125**

O opcional VLT® BACnet/IP MCA 125 é uma solução plug-and-play que otimiza o uso do VLT® HVAC Drive junto com sistemas de gerenciamento predial (BMS) que utilizem o protocolo BACnet/IP ou executem BACnet em Ethernet.

O interruptor gerenciado de três portas integrado do opcional VLT® BACnet/IP MCA 125 inclui duas portas Ethernet externas e uma porta Ethernet interna. Este interruptor permite o uso da estrutura de linha para o cabeamento Ethernet, que está se tornando cada vez mais atraente para instalações modernas.

**134B8493** **TRANSDUTOR PARA CONVERSOR FREQUENCIA**

CBM Transducer 0-25mm/s RMS 4-20mA

**134B8496** **CABO PARA CONVERSOR FREQUENCIA**

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Peças de Reposição

Image
coming
soon**176F3548** **Cover DC Link Coil Large Dh Frame**

Cover DC Link Coil Large Dh Frame

**176F3540** **Dissipador de calor Frames Dh****176F3737** **KIT SENSOR DE CORRENTE 500A**

Spare part for VLT: 500A Current Sensor Conversion Kit

**176F3329** **CABO DE ALIMENTACAO PARA GATE D2H/D4H****176F3327** **CABO CART. POT HF/RFI D2h/D4h**

Cable Power Card to HF/RFI D2h/D4h

**176F3325** **CABO PARA CARTAO DE POTENCIA D2H-D4H****176F3323** **Cable Power Card to CT D2h/D4h**

For use on drives produced in week 50, 2015 or earlier.

**176F3321** **Cable Power Card to Door Fan D2h/D4h****176F3319** **CABO FLAT P CART POT P CONVREQ D2H/D4H****For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Peças de Reposição

**176F3386** **BARRAMENTO PARA BANC CAP 400V D2H/D4H**

To be used on the following frame sizes

D-frame: Drives produced before week 18, 2018 with production site "H" indicated by the character preceding the last 3 characters of the serial number (H188)

**176F3434** **Desconexão 600A 690 V**

Main disconnect

**176F3427** **Capac amort IGBT 1250V 1,0UF mont amp**

IGBT snubber cap, mounts on brake IGBT modules

**176F3353** **Filtro vent. porta chassi Dxh, pct c/ 10**

IP21/IP54 door filter 3 per drive, 10 per kit

**176F3345** **CABO CLAMP 45MM P CONV. DE FREQ DH FRAME****176F3344** **SUPORTE GATE DRIVE D2H/D4H****176F3342** **TAMPA PARA CONVERSOR DE FREQUENCIA****176F3336** **CABO DE IRRUPÇÃO PARA SCR D2H/D4H****176F3332** **CABO DE GATILHO DO CARTAO INRUSH D2H/D4H****176F3385** **BARRAMENTO PARA CONVERSOR DE FREQUENCIA**

For use on drives produced in week 2, 2016 or earlier.

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Peças de Reposição

**176F3383** **BARRAMENTO PARA CONVERSOR DE FREQUENCIA****176F3382** **Bus Bar DC+ Inductor to CAP Bank D2h/D4h****176F3381** **Bus Bar DC- SCR to DC Coil D2h/D4h**

Bus Bar DC- SCR to DC Coil D2h/D4h

**176F3380** **Bus Bar DC+ SCR to DC Coil D2h/D4h**

Bus Bar DC+ SCR to DC Coil D2h/D4h

**176F3379** **BARRAMENTO SCR DC D2H/D4H**

Used on the below listed drives built before week 27 of 2012.

FC-302 N200 T5

FC-102 N250 T4

FC-202 N250 T4

For drives of the above listed sizes built after week 27 of 2012 use

176F3378. See Product Note 185 for more information.

**176F3378** **BARRAMENTO SCR DC D2H/D4H**

Used on the below listed drives built after week 27 of 2012.

FC-302 N200 T5

FC-102 N250 T4

FC-202 N250 T4

For drives of the above listed sizes built before week 27 of 2012 use

176F3379. See Product Note 185 for more information.

**176F3377** **BARRAMENTO PARA CONVERSOR DE FREQUENCIA**

Used on the below listed drives built before week 27 of 2012.

FC-302 N200 T5

FC-102 N250 T4

FC-202 N250 T4

For drives of the above listed sizes built after week 27 of 2012 use

176F3376. See Product Note 185 for more information.

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Peças de Reposição

**176F3376** **BARRAMENTO AC DE ENTRADA D2H/D4H**

Used on the below listed drives built after week 27 of 2012.

FC-302 N200 T5

FC-102 N250 T4

FC-202 N250 T4

For drives of the above listed sizes built before week 27 of 2012 use

176F3377. See Product Note 185 for more information.

**176F3375** **KIT VENTILAÇÃO NA PORTA IP21/IP54****176F3374** **BARRAMENTOS PARA CONVERSOR DE FREQUENCIA****176F3373** **BARRAMENTOS PARA CONVERSOR DE FREQUENCIA****176F3372** **BARRAMENTO PARA CONVERSOR DE FREQUENCIA****176F3371** **BARRAMENTO TERM.S FUSIVEL S RFI D2H/D4H**

Bus Bar Mains,no Fuse,no RFI D2h/D4h

**176F3370** **ISOLACAO TERMIN. DO MOTOR DRIVES D2H/D4H**

Insulation Motor Terminals D2h/D4h

**176F3369** **FOLHA PROTECAO PARA CONVERSOR FREQUENCIA****176F3368** **BARRAMENTOS DOS TERMINAIS DE SAIDA**

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Peças de Reposição

**176F3365** **MODULO DUPLO IGBT 900AMP T4/T5 DRIVE****176F3361** **Bracket Inrush Support D2h/D4h****176F6634** **CAPACITOR T5**

To be used on the following frame sizes

D-frame: Drives produced during or after week 18, 2018 with production site "H" indicated by the character preceding the last 3 characters of the serial number (H188)

E-frame: Any datecode

**176F8348** **CHAVE SECCIONADORA FRAME D2****176F5724** **DC Link Coil large Dh Frame 65uH**

DC Link Coil large Dh Frame 65uH

**176F6520** **Cable Power Card to CT D2h/D4h**

Para uso em drives datados da semana 51 de 2015 ou posteriormente.

**176F6447** **Sensor de corrente 500 A-FX10**

Tamanhos do gabinete D2h, D4h, D7h e D8h:

DTC 302 - compatível com todos.

Todos os outros - Para uso em drives produzidos na semana 3 de 2016 ou posteriormente.

Tamanhos do gabinete E1, E2, F1, F2, F3, F4, F8, F9, F10, F11, F12, F13, F18:

Para uso em drives datados da semana 16 de 2016 ou posteriormente.

**176F3178** **CABO DE SINAL PARA GATE DE IGBT D2H D4H****176F3176** **CABO DE SINAL PARA GATE DE IGBT D2H D4H****For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Peças de Reposição

**176F3174** **Fusível 800A 700 V de corpo quadrado**

Mains fuse, 1 per kit

**176F3169** **Ventilador de porta IP54 CC 120X38 48VCC**

IP21/54, door fan, 120x38mm, 48VDC, fan only

**176F3167** **Ventilador superior IP20 CC 80X38 48VCC**

IP20, top fan, 80x38mm, 48VDC, fan only

**176F3165** **Ventilador de mistura CC 40X28 24 VCC**

Mixing fan, mounted below the input terminals

**176F3164** **DISSIPADOR DO VENTILADOR DC, DIMENSOES 1****176F3163** **CAPACITOR 4700uF 450V**

To be used on the following frame sizes

D-frame: Drives produced before week 18, 2018 with production site "H" indicated by the character preceding the last 3 characters of the serial number (H188)

**176F3162** **Capac amort IGBT 1000V 1,5uF mont amp**

IGBT snubber cap, mounts on IGBT modules

**176F3161** **CARTÃO DE BALANÇO 110-315KW 400V****176F3160** **CARTAO DE DISPARO P/ DRIVE NO 110-315kW****176F3159** **CARTAO DE PRE-CARGA 110-315KW 400V****For more information, please use this link to visit the product page on Danfoss Product Store** 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Peças de Reposição

**176F3158** **Cartão de escala da corrente de 4,22 ohm**

Installs on the power board

**176F3139** **CARTAO DE POT.NO 315KW 380-480V**

x10

130B9001 **CONECTOR P/ CONVERSOR DE FREQUENCIA****130B0295** **EMBALAGEM COM ACESSORIOS CONTENDO PLUGS****130B1069** **MULTIPLS PLUGUES DO RELE 1**

spare, 3 pole connector, relay 1, fc300

**130B1068** **MULTIPLS PLUGUES DO RELE 2**

spare, 3 pole connector, relay 2, fc300

**130B1107** **DISPLAY GRÁFICO P/ VLT FC**

VLT Control Panel LCP 102

Display de gráfico iluminado com texto simples.

Compatível com todos os idiomas e caracteres de texto.

Quick menu para rápida colocação em funcionamento.

Função salvar e copiar dos conjuntos de parâmetros.

Ajuda on-line para todas as funções.

**134B1730** **CARTAO DE CONTROLE SEM SAFE STOP FC-102**

Compatível com a versão de software 5.21 ou superior. Se seu drive tem um software específico do cliente ou uma versão de software de marca, solicite o cartão de controle com número de peça 130B1151

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Peças de Reposição

Image
coming
soon**176F6767** **BARRAMENTO TERM. BANCO CAP 400V D2H/D4H**

Para ser usado nos seguintes tamanhos do gabinete

Drives com tamanho do gabinete D datados da semana 18 de 2018 ou posteriormente, com o local de produção "H". O local de produção é indicado pelo caractere anterior aos últimos 3 caracteres do número de série (por exemplo, H188)

**176F3890** **KIT TRANSISTOR P/ CONVERSOR FREQUENCIA**

568A SCR Retrofit Kit - N200T5/N250T5 HO

Image
coming
soon**176F3860** **MODULO RETIFICADOR P/ CONVERSOR FREQ.**

Rectifier SCR/Diode 586A 1600V

**176F4183** **Bsr Crnt Sensor D2h/D4h - 500A LEM, HEX**

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.