

The new part, as of 01.01.2015, is blocked for delivery. Spare part can continue to be purchased as required, but price may deviate from new part. Further information under SIMATIC current entry ID: 109486162. For questions, the familiar contact persons are available to you. SIMATIC MP 277 10" Touch Multi Panel with retentive memory 10.4" TFT display 6 MB configuration memory configurable with WinCC flexible 2005 Standard SP1



General information	
Product type designation	MP277 10" touch
Customer-specific configuration	Yes
Display	
Design of display	TFT
Screen diagonal	10.4 in
Color display	Yes
Number of colors	65 536
Resolution (pixels)	
• Horizontal image resolution	640 pixel
• Vertical image resolution	480 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Touch screen
Keyboard fonts	
• Function keys	
— Number of function keys	0
— Number of function keys with LEDs	0
• System keys	No
— Number of system keys	0
• Numeric keyboard	Yes
• alphanumeric keyboard	Yes
• hexadecimal keyboard	Yes
Touch operation	
• Design as touch screen	Yes; analog, resistive
Connection type	
• Type of connection for mouse/keyboard/barcode reader	USB / USB / USB
Installation type/mounting	
Mounting position	vertical
maximum permissible angle of inclination without external ventilation	35°
Supply voltage	
Type of supply voltage	DC
Processor	
Processor type	ARM
Memory	
Type of memory	Flash / RAM
Memory available for user data	6 Mbyte
Capacity of main memory, max.	128 Mbyte

Time of day	
Clock	
• Type	Hardware clock, battery backup, synchronizable
• retentive	Yes
• synchronizable	Yes
Interfaces	
Interfaces/bus type	1x RS 422, 1x RS 485, 1x Ethernet (RJ45)
Number of industrial Ethernet interfaces	1
Number of RS 485 interfaces	1
Number of RS 422 interfaces	1
Number of USB interfaces	2; Up to 1 GB
Multimedia card/SD card slot	1x Multimedia Card slot, up to 128 MB
With software interfaces	No
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
PROFIBUS	Yes
EtherNet/IP	No
Protocols (Ethernet)	
• TCP/IP	Yes
Further protocols	
• MODBUS	Yes
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	NEMA 4x (when installed)
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
Suitable for safety functions	No
Use in hazardous areas	
• ATEX Zone 2	No; certificate no longer available as of 1 October 2020
• ATEX Zone 22	No; certificate no longer available as of 1 October 2020
• FM Class I Division 2	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	90 %
Operating systems	
pre-installed operating system	Windows CE
configuration / header	
Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes
Configuration software	
• Configuration tool	WinCC flexible Standard Version 2005 SP1 or higher (to be ordered separately)
• STEP 7 Basic (TIA Portal)	No
• STEP 7 Professional (TIA Portal)	No
• WinCC flexible Compact	No
• WinCC flexible Standard	Yes
• WinCC flexible Advanced	Yes
• WinCC Basic (TIA Portal)	No

- WinCC Comfort (TIA Portal) Yes
- WinCC Advanced (TIA Portal) Yes
- WinCC Professional (TIA Portal) Yes

Languages

Online languages

- Number of online/runtime languages 16

Project languages

- Languages per project 32

Functionality under WinCC (TIA Portal)

Libraries Yes

Task planner Yes

Help system Yes

- Number of characters per info text 80

Message system

- Number of alarm classes 32
- Number of messages 4 000
- Bit messages Yes
 - Number of bit messages 4 000
- Analog messages Yes
 - Number of analog messages 200
- System messages HMI Yes
- System messages PLC Yes
- System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ...) Yes
- Lines 1
- Number of characters per message 80
- Number of process values per message 8
- Acknowledgment groups Yes
- Message indicator Yes
- First/last value Yes

Recipe management

- Number of recipes 300
- Data records per recipe 500
- Entries per data record 1 000
- Recipe memory 64 KB integrated Flash, expandable

Variables

- Number of variables per device 2 048
- Number of variables per screen 200
- Number of variables 1 000
- Type Date & Time 2 048
- Limit values Yes
- Multiplexing Yes
- Structures Yes

Images

- Number of configurable images 500
- Permanent window/default Yes
- Start screen configurable Yes
- Image selection by PLC Yes
- Image number in the PLC Yes

Image objects

- Text objects 10 000 text elements
- Number of I/O fields per image 200
- Number of date/time fields 200
- Return Yes
- Graphics object Bit maps, icons, vector graphics
 - Icons 1 000

Complex image objects

- Status/control With SIMATIC S7
- dynamic objects Diagrams, bar graphs, sliders, analog display, invisible buttons
 - Number of objects per project 1 000
 - Number of curve diagrams per image 10

• Methods	Trend / profile
• Bar graphs — Number of bars per chart	10
• Sliders — Number of slides per image	10
• Pointer instruments — Number of analog indicators per image	10
• Limit value lines	Yes
• Number of alphanumerical fields — alphanumeric fields per image	300 200
• Number of numerical fields — numerical fields per image	2 048 200
• Number of password fields	2 048
• Number of visible switches per project — visible switches per image — hidden switches per image	200 200 200
• Number of status switches per project — Number of status switches per image	200 200
• Number of selector switches per project — Selector switches per image	200 200
• Number of decade switches per project — Decade switches per image	200 200
• Number of signal lamps per project — Signal lamps per image	200 200
Attributes for dynamic objects	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
Lists	
• Number of text lists per project	500
• Number of text lists per image	200
• Number of entries per text list	256
• Number of graphics lists per project	400
• Number of graphic lists per image	200
• Number of entries per graphics list	256
Archiving	
• Number of archives per device	20
• Number of measuring points per project	20
• Number of entries per archive	10 000
• Message archive	Yes
• Process value archive	Yes
• Archiving methods — Sequential archive — Short-term archive	Yes Yes
• Memory location	SD and MultiMediaCard
• Data storage format — CSV	Yes
• Online evaluation — using trend curves	Yes
Filters	
• cyclic	Yes
• Tolerance	Yes
• Change	Yes
Security	
• Number of user groups	50
• Number of user rights	32
• Password export/import	Yes
Logging through printer	
• Recording/Printing	Alarms, report (shift report), color print, hardcopy
Transfer (upload/download)	
• Transfer of configuration	MPI/PROFIBUS DP, USB, Ethernet, automatic transfer recognition

Process coupling			
• Connection to controller		S5, S7-200, S7-300/400, TI 505, SINUMERIK, SIMOTION, Allen Bradley (DF1), Allen Bradley (DF485), Mitsubishi (FX), OMRON (LINK/Multilink), Modicon (Modbus) see chapter "System interfaces"	
• S7-1200		Yes	
• S7-1500		Yes	
• S7-200		Yes	
— PPI (point-to-point)		Yes	
— PPI network		Yes	
— MPI		Yes	
— PROFIBUS DP		Yes	
— Ethernet		Yes	
• S7-300/400		Yes	
— MPI		Yes	
— PROFIBUS DP		Yes	
— PROFINET		Yes	
• S5		Yes	
— PROFIBUS DP		Yes	
• TI 505		Yes	
• Allen Bradley (DF1)		Yes	
• Allen Bradley (DF485)		Yes	
• Mitsubishi (FX)		Yes	
• Mitsubishi (MP4)		Yes	
• Telemecanique (Uni-Telway)		Yes	
• OMRON (LINK/Multilink)		Yes	
• Modicon (Modbus)		Yes	
• GE-Fanuc (SNP)		Yes	
Functions			
• TAB sequence		Yes	
• Calculating functions		Yes	
• Animate		Yes	
Service tools/configuration aids			
• Clean screen		Yes	
• Touch calibration		Yes	
• Backup/Restore manually		Yes	
• Simulation		Yes	
• Device switchover		Yes	
• Delta transfer		Yes	
Expandability/openness			
• Open Platform Program		Yes	
Peripherals/Options			
Peripherals		Printer, barcode reader	
SIMATIC HMI MM memory card: Multi Media Card		Yes	
SIMATIC HMI SD memory card: Secure Digital memory card		Yes	
USB memory		Yes	
Additional software components loadable		Yes	
Dimensions			
Width of the housing front		335 mm	
Height of housing front		275 mm	
Mounting cutout, width		310 mm	
Mounting cutout, height		248 mm	
Overall depth		61 mm	
Weights			
Weight (without packaging)		2.65 kg	
Other			
free hotline		Yes	
Classifications			
		Version	Classification
	eClass	14	27-33-02-01
	eClass	12	27-33-02-01

eClass	9.1	27-33-02-01
eClass	9	27-33-02-01
eClass	8	27-24-23-02
eClass	7.1	27-24-23-02
eClass	6	27-24-23-02
ETIM	10	EC001412
ETIM	9	EC001412
ETIM	8	EC001412
ETIM	7	EC001412
IDEA	4	6607
UNSPSC	15	43-21-15-06

Approvals / Certificates	
General Product Approval	EMV

[Manufacturer Declaration](#)






For use in hazardous locations	Radio Equipment Type Approval Certificate	Maritime application
--------------------------------	---	----------------------


[FM](#)
[Miscellaneous](#)


[NK / Nippon Kaiji Kyokai](#)

Maritime application



last modified:

4/4/2025