

acessórios para barras 3NJ41 barras seccionadoras em carga de segurança tam. NH1-3 transformador integrável 250/1A, cl. 0,5



Figure similar

Versão	
nome da marca do produto	SETRON
designação do produto	Conversor de corrente
versão do produto	acessórios para interruptor-seccionador de fusíveis 3NJ41
tensão de serviço	0,72 kV
tensão de isolamento valor nominal	3 kV
designação do fator limitativo de sobrecorrente	FS 5
corrente	
• na entrada valor nominal	250 A
range de valores da frequência de operação	50/60 Hz
Classe de proteção	
grau de proteção IP	IP20
Projeto mecânico	
altura	80 mm
largura	52 mm
profundidade	26 mm
Peso líquido por ME	0,209 kg
Condições ambientais	
temperatura ambiente durante operação	
• mínimo	-10 °C
• máximo	55 °C
Homologações certificados	
Environment	General Product Approval

[Environmental Conformations](#)



Outras informações

Informações sobre a embalagem

[Informações sobre a embalagem](#)

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/pt/pt/Catalog/product?mlfb=3NJ4915-2GA10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pt/ps/3NJ4915-2GA10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ4915-2GA10

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Curvas características

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

última alteração:

13/06/2025 

