




Accessory 3WA/3WL Shunt trip (ST) 5% OP, 24-30 V DC momentary duty, with cut-off switch, not for continuous duty

Model	
product brand name	SENTRON
product designation	shunt release
design of the product	shunt release (ST) 5% OP, 24 to 30 V DC for momentary duty, with cut-off switch, no continuous duty possible
design of the fuse link	fuse: 10 A, miniature circuit breaker C characteristic: 10 A
closing active power [W]	300 W
opening time (electrical) of circuit breaker at $U_s = 100\%$	50 ms
ambient temperature during operation	• minimum -40 °C • maximum 70 °C
ambient temperature during storage	• minimum -40 °C • maximum 80 °C

Approvals Certificates	
General Product Approval	Test Certificates



[Confirmation](#)



[Special Test Certificate](#)

Test Certificates	Marine / Shipping	other
-------------------	-------------------	-------

[Type Test Certificates/Test Report](#)



[Confirmation](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA9111-0AD22>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WA9111-0AD22>



Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA9111-0AD22

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications



last modified:

9/9/2024 

