

acessórios para barras 3NJ41 barras seccionadoras em carga de segurança tam. NH1-3 transformador integrável 75/1A, cl. 1



Figure similar

Versão	
nome da marca do produto	SETRON
designação do produto	Conversor de corrente
versão do produto	acessórios para interruptor-seccionador de fusíveis 3NJ41
tensão de serviço	0,72 kV
tensão de isolamento valor nominal	3 kV
designação do fator limitativo de sobrecorrente	FS 5
corrente	
• na entrada valor nominal	75 A
range de valores da frequência de operação	50/60 Hz
Classe de proteção	
grau de proteção IP	IP20
Projeto mecânico	
altura	80 mm
largura	52 mm
profundidade	26 mm
Peso líquido por ME	215 g
Condições ambientais	
temperatura ambiente durante operação	
• mínimo	-10 °C
• máximo	55 °C
Homologações certificados	
Environment	General Product Approval

[Environmental Conformations](#)



Outras informações

Informações sobre a embalagem

[Informações sobre a embalagem](#)

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/pt/pt/Catalog/product?mlfb=3NJ4915-2DA20>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pt/ps/3NJ4915-2DA20>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ4915-2DA20

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Curvas características

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

última alteração:

13/06/2025 

