


2722852

https://www.phoenixcontact.com/us/products/2722852

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.





### Commercial data

Item number	2722852
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	DR16
Product key	DRSAAA
GTIN	4017918141202
Weight per piece (including packing)	486.4 g
Weight per piece (excluding packing)	486.4 g
Customs tariff number	85389091
Country of origin	DE



2722852

https://www.phoenixcontact.com/us/products/2722852

### Technical data

Product type	PLC controller board
Format	6 rack units, 1 slot

### System properties

IEC 61131 runtime system

Data storage system	MPM, base address adjustable	
INTERBUS-Master		
Number of devices with parameter channel	max. 62	
Local diagnostics		
Monitored function	Operating status	
Optical representation	3 LEDs	

### Electrical properties

Local diagnostics	Operating status 3 LEDs	
	Error status 2 LEDs	
Transmission medium	Copper	
Maximum power dissipation for nominal condition	max. 3 W	
Supply		
Supply voltage	5 V DC	
Supply voltage range	4.9 V DC 5.3 V DC	
Residual ripple	0.1 V <sub>PP</sub>	
Typical current consumption	590 mA	

#### Connection data

Connection method	Via VMEbus connector P1

#### Interfaces

Interrupts	Level 1-7, vector 0 - 255	
INTERBUS remote bus		
Connection method	9-pos. D-SUB female connector (optionally optical fiber possible via interface converters) with electrical isolation	
Parameterization/operation/diagnostics		
Connection method	RS-232-C, D-SUB 9-pos. male connector	
Host system		
Connection method	VMEbus systems, VMEbus connector P1 (IEC 603-2)	

### Environmental and real-life conditions



2722852

https://www.phoenixcontact.com/us/products/2722852

/	Ambient conditions	
	Degree of protection	IP00
Mounting		
Мс	unting	



2722852

https://www.phoenixcontact.com/us/products/2722852

### Classifications

### **ECLASS**

ECLASS-11.0 27242208



2722852

https://www.phoenixcontact.com/us/products/2722852

## Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes	
Exemption	6(a), 6(a)-I, 6(c), 7(a), 7(c)-I	
China RoHS		
Environment friendly use period (EFUP)	EFUP-50	
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	



2722852


https://www.phoenixcontact.com/us/products/2722852

#### Accessories

### IBS PRG CAB - Connecting cable

2806862

https://www.phoenixcontact.com/us/products/2806862





### IBS MC FLASH 2MB - Memory

2729389

https://www.phoenixcontact.com/us/products/2729389

Program and configuration memory, 2 Mbyte





2722852

https://www.phoenixcontact.com/us/products/2722852

### DIAG+ - Configuration and diagnostic software

2730307

https://www.phoenixcontact.com/us/products/2730307



Diag+, diagnostic software for INTERBUS and PROFINET networks, additional areas of application are, for example, commissioning and maintenance.

### IBS CMD SWT G4 E - Configuration and diagnostic software

2721442

https://www.phoenixcontact.com/us/products/2721442



Network configuration software for INTERBUS Generation 4



2722852

https://www.phoenixcontact.com/us/products/2722852

### IBS CMD SWT G4 - Configuration and diagnostic software

2721439

https://www.phoenixcontact.com/us/products/2721439



Network configuration software for INTERBUS Generation 4

### IBS MC FLASH 2MB - Memory

2729389

https://www.phoenixcontact.com/us/products/2729389

Program and configuration memory, 2 Mbyte



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com