

Kinetix VP Servo Motors

[VPL-B0753E-CK12AS](#)



Representative Rendering, Not The Actual Product

VPL Low Inertia Motors, 480V AC, 75mm Bolt Circle Frame Size, 3 (Three) Magnet Stacks, E Winding, 3300-3900 RPM Rated Speed, 18 bit Single-turn Digital High Resolution Encoder, Keyless Shaft, Single SpeedTec Din Connector, No Holding Brake, , IP66 Shaft Seal Fitted

Product Details

PRODUCT SELECTION	
Bulletin Number	VPL Low Inertia Motors
Voltage Class	480V AC
Frame Size	75mm Bolt Circle Frame Size
Stack Length	3 (Three) Magnet Stacks
Rated Speed	E Winding, 3300-3900 RPM Rated Speed
Feedback	18 bit Single-turn Digital High Resolution Encoder
Shaft Extension	Keyless Shaft
Connectors	Single SpeedTec Din Connector
Brake Option	No Holding Brake
Mounting	IEC Metric Mounting Flange
Factory Options	IP66 Shaft Seal Fitted
Torque Rating	Torque Rating

Supporting Documentation and Downloads

- [Product Profile \(Web page\)](#)
- [Motion Control Selection Guide \(Web page\)](#)
- [Installation Instructions \(Web page\)](#)
- [Rotary Motion Specifications Technical Data](#)
- [Motion Accessories Specifications Technical Data](#)
- [Photo](#)
- [Link to 3D model from Motion Analyzer](#)